

AD-A046 053

DECISION SYSTEMS DAYTON OH F/G 15/5  
THE INVENTORY SYSTEM SIMULATOR (INSSIM). VOLUME II PROGRAM LIST--ETC(U)  
AUG 77 W S DEMMY F49620-77-C-0063

UNCLASSIFIED


RM-77-03

AFOSR-TR-77-1235

NL

1 of 2  
ADA  
046053





NATIONAL BUREAU OF STANDARDS  
MICROCOPY RESOLUTION TEST CHART



3

18 AFOSR

19 TR-77-1235

9 Technical Rept.,

Approved for public release;  
distribution unlimited.

6 THE INVENTORY SYSTEM SIMULATOR  
(INSSIM).  
VOLUME II, PROGRAM LISTINGS AND NARRATIVES.

15 F49620-77-C-0063

16 2304 by 17 A5

10 W. Steven Denny

11 August 1977

DDC  
NOV 3 1977  
RECEIVED

12 119p.

AIR FORCE OFFICE OF SCIENTIFIC RESEARCH (AFSC)  
NOTICE OF TRANSMITTAL TO DDC  
This technical report has been reviewed and is  
approved for public release under AFR 190-12 (7b).  
Distribution is unlimited.  
A. D. FLOSE  
Technical Information Officer

14 RM-77-93  
Decision Systems  
3575 Charlene Drive  
Dayton, Ohio 45432

1473  
393 082



# TABLE OF CONTENTS

## I. INTRODUCTION

## II. PROGRAM LISTINGS AND NARRATIVES

### ROUTINES

BUDGET	LEVEL
CANCLB	LEVELN
CUM	MAIN
CUMB	ORDER
DEMPAR and GETREQ	OUT
ENTER	OUTCST
ENTERB	PLOTR
FILLBO	RANDU
FOR576	RECLIV
FORUPD	REMOVE
GP	REQ
GUIDE	RET
INBUDG1	SSTAT
INFEL	STATUS
INITAL	STATN
INITEM	WRIFEL
ITRSLT	TERMIN
	ZERO

ACCESSION for

NTIS ☒ Write Section

DDC ☐ B.H. Section

UNANNOUNCED

JUSTIFICATION

BY

DISTRIBUTION/AVAILABILITY NOTES

DATE

A 232

## CHAPTER I. INTRODUCTION

9/5/2 This is the second of two volumes describing the features of the Inventory System Simulator (INSSIM). INSSIM is a FORTRAN-based model of a general single-echelon inventory system. The model was specifically designed to evaluate alternative forecasting and inventory management policies proposed for use in the EOQ Buy Computation System (D062). Volume I of this report describes the philosophy, organization, and input/output features of INSSIM. This volume documents the statement listings of each INSSIM program, and provides narratives describing the function of each of these routines.

The routines are presented in alphabetical order. Documentation for each routine consists of a program narrative, and a listing of the FORTRAN code for that routine. Additional comments are included as a part of the FORTRAN code for the more complex routines. Definitions of major INSSIM variables are documented in Volume I, and familiarity with the contents of Volume I is assumed.

C

CHAPTER II. PROGRAM LISTINGS AND NARRATIVES

Subroutine: BUDGET

Function:

This routine updates period counters and obligation accumulators, and creates two budget review events.

Description:

This routine is called at the conclusion of each budget revision interval. It zeros the accumulator IOBLIG used to record obligations within the current budget period. It then creates type 6 and type 7 events, and puts these events on the Future Events List. These events are used to revise buy guidelines within the budget period, and to signal the beginning of a new budget period, respectively. Finally, the budget period counter, NBPER, is incremented.

1 12-08-76 20,399

BUDGET

p 2 of 1

```

SUBROUTINE BUDGET
C   AT THE CONCLUSION OF EACH BUDGET REVISION INTERVAL, THIS ROUTINE
C   IS CALLED TO UPDATE PERIOD COUNTERS AND OBLIGATION ACCUMULATORS
COMMON/IOBLIG/IOBLIG
COMMON/ITHQ/ITHQ
COMMON/IDTHQ/IDTHQ
COMMON/NBPER/NBPER
COMMON/ITDIV/ITDIV
COMMON/ITIME/ITIME
C   RESET COUNTERS AND CALL GUIDE TO RESET GUIDELINES
IOBLIG=0
ITDIV=ITIME+13
CALL ENTER(ITDIV,7,0,0,0)
C   PLACE BUDGET REVIEW TRANSACTION ON FT LIST
12 ITHQ=ITHQ+IDTHQ
CALL ENTER(ITHQ,8,0,0,0)
C   UPDATE PERIOD COUNTER
NBPER=NBPER+1
RETURN
END
```

Subroutine: CANCLB

Function:

This routine simulates the cancellation of backorders by customers which have been forced to wait an unacceptably long period of time.

Description:

When this routine is called, the stock status of each item being simulated is reviewed. If any item has a backorder that is older than MBODAYS days, routine CANCLB takes action to reflect cancellation of the associated requisition by the requesting customer. To do this, data elements defining the backorder are removed from the Backorder File, and Subroutine CUM is called to update the associated performance statistics. Statistics affected are: IRATON, ICANCL, IBACKT, and IBACKI.

Finally, CANCLB creates a new type 3 event to occur at time ITCANB plus IDCANB.



01 12-08-76 19.916

CANCLB  
P. 1 of 2

```
SUBROUTINE CANCLB
COMMON/IBACPT/IBACPT(200)
COMMON/ICANCL/ICANCL(30,3)
COMMON/IPRIOR/IPRIOR(200)
COMMON/IQTYB/IQTYB(200)
COMMON/ITMBAC/ITMBAC(200)
COMMON/ILOCBK/ILOCBK(200)
COMMON/NLOCBK/NLOCBK
COMMON/NBOPT/NBOPT(50)
COMMON/NBOTU/NBOTU(50)
COMMON/ITIME/ITIME
COMMON/ITDAY/ITDAY
COMMON/MBODAY/MBODAY
COMMON/ITCANB/ITCANB,IDCANB
COMMON/IDBUG/IDBUG
COMMON/NITEM/NITEM
COMMON/IBACKT/IBACKT(30,3)
COMMON/IBACKI/IBACKI(30,3)
COMMON/IRATON/IRATON(30,3)
DO 500 N=1,NITEM
50 CONTINUE
IPT=NBOPT(N)
JPT=IPT

C
C      ARE THERE ANY BACKORDERS ON ITEM N
C
100 CONTINUE
IF(NBOPT(N).LE.0) GO TO 500
110 CONTINUE
C      COMPUTE BACKORDER AGE IN DAYS
IAGE=(ITIME-ITMBAC(JPT))/ITDAY
IF(IAGE.GT.MBODAY) GO TO 150

C
C      IS JPT THE LAST BACKORDER ON THE CHAIN
140 IF(IBACPT(JPT).LE.0) GO TO 500
C      UPDATE INDICES
IPT=JPT
JPT=IBACPT(JPT)
GO TO 110

C
C      CANCEL BACKORDER LOCATED AT JPT
C
C
C      UPDATE STATISTICS TO REFLECT CANCELATION
150 CONTINUE
IQTY=IQTYB(JPT)
JQTY=-IQTY
NBOTU(N)=NBOTU(N)-IQTY
CALL CUM(IRATON,IQTY,N)
1457 DO LOOP INDEX N MAY NOT BE REDEFINED IN CALL OR ABNORMAL FUNCTION
CALL CUM(ICANCL,IQTY,N)
1457 DO LOOP INDEX N MAY NOT BE REDEFINED IN CALL OR ABNORMAL FUNCTION
```

01 12-08-76 19.916

CANCLB

P 2 of 2

```
      CALL CUM(IBACKT,JQTY,N)
1457 DO LOOP INDEX N MAY NOT BE REDEFINED IN CALL OR ABNORMAL FUNCTION
      IF(IPRIOR(JPT).EQ.1) CALL CUM(IBACKI,JQTY,N)
1457 DO LOOP INDEX N MAY NOT BE REDEFINED IN CALL OR ABNORMAL FUNCTION
      IF(IDBUG.NE.1) GO TO 160
      WRITE(6,8000)ITIME,N,IQTY,IPRIOR(JPT),ITMBAC(JPT),JPT
8000 FORMAT(7H CANCEL,I10.5I8)
160 CONTINUE
C      RECORD LOCATION JPT AS AVAILABLE FOR FILING OTHER BACKORDER DAT
      NLOCBK=NLOCBK+1
      ILOCBK(NLOCBK)=JPT
C      IS JPT THE FIRST BACKORDER ON THE CHAIN
      IF(JPT.NE.NBOPT(N)) GO TO 170
      NBOPT(N)=IBACPT(JPT)
      GO TO 50
C      IS JPT THE LAST ENTRY ON THE CHAIN
170 CONTINUE
      IF(IBACPT(JPT).NE.0) GO TO 180
C      SET IPT AS LAST ON THE CHAIN
      IBACPT(IPT)=0
      GO TO 500
180 CONTINUE
C      THEN JPT IS IN THE MIDDLE OF THE CHAIN
      IBACPT(IPT)=IBACPT(JPT)
      JPT=IBACPT(IPT)
      GO TO 110
C
C      CREATE NEXT REVIEW EVENT
C
500 CONTINUE
      ITCANB=ITCANB+IDCANB
      CALL ENTER(ITCANB,3,0,0,0)
      RETURN
      END
```



Subroutine: CUM

Function:

This routine updates the action, units, and dollar counts associated with the statistic ISTAT.

Description:

The variable KFSN defines the number of the items involved and IQTY defines the associated quantity. If IQTY is negative, the action count is decreased by one. The units and dollar counts are always increased.

92-11-71 10.619

CUM

P. 1 of 1

```

SUBROUTINE CUM(ISTAT, IOTY, KFSN)
C      THIS ROUTINE UPDATES THE ITEMS, UNITS, AND DOLLAR COUNTS
C      ASSOCIATED WITH THE STATISTIC ISTAT
      DIMENSION ISTAT(50,3), UCOST(50)
      COMMON/ITINV/ITINV
      COMMON/UCOST/UCOST
      COST=UCOST(KFSN)
      I=ITINV
      IF(IOTY.EQ.0) GO TO 21
      ISTAT(I,1)=ISTAT(I,1)+1
      GO TO 22
21  ISTAT(I,1)=ISTAT(I,1)-1
22  ISTAT(I,2)=ISTAT(I,2)+IOTY
      DOLLAR=COST*FLOAT(IOTY)
      ISTAT(I,3)=ISTAT(I,3)+FLOAT(DOLLAR)
      RETURN
      END
```

Subroutine: CUMB

Function:

This routine updates the units and dollar counts associated with statistic ISTAT. The actions count is not affected.

Description:

The variable KFSN defines the number of items involved and IQTY defines the associated quantity. When called, Subroutine CUMB updates the units and dollar counts of statistic ISTAT. The actions/FSN count is not affected.

02-11-77 19.698

CUMB,  
p. 1 of 1

```
SUBROUTINE CUMBC(ISTAT, TOTY, KFSN)
C      THIS ROUTINE UPDATES THE UNITS AND DOLLAR COUNTS ASSOCIATED
C      WITH STATISTIC ISTAT. THE ACTIONS COUNT IS NOT EFFECTED
      DIMENSION ISTAT(40,3), UCOST(50)
      COMMON/ITINVZ/ITINV
      COMMON/UCOSTZ/UCOST
      COST=UCOST(KFSN)
      IT=ITINV
      ISTAT(1,2)=ISTAT(1,2)+TOTY
      DOLLAR=COST*FLOAT(TOTY)
      ISTAT(1,3)=ISTAT(1,3)+IT*IX(DOLLAR)
      RETURN
      END
```

Subroutine: DEMP PAR

Function:

Subroutine DEMP PAR is called at the beginning of each simulation quarter to generate the specific requisition and serviceable return events to occur in the current quarters.

Description:

In DEMP PAR, the variable IDPER is first incremented. This variable defines the historical period in the Demand Driver File to be used in generating demand activity in the current quarter.

Next, DEMP PAR generates type 4 event to represent the arrival of serviceable returns within the quarter. At present, it is assumed that all serviceable returns are generated one month after the beginning of the quarter.

Subroutine DEMP PAR next generates specific requisition events to occur in the current quarter, and places these events on the Future Events List. Subroutine GETREQ is used to generate requisition sizes with the same probability distributions as observed in AFLC inventory systems. See Volume I, Chapter VI, for a detailed discussion of the demand generation process.

Finally, DEMP PAR generates a type 12 event to occur at a time IDPER in the future, and places this event on the Future Events List. This action causes the next call to DEMP PAR.

DEMPAR

1 8 3

```

20      IDENT      WP1279,XRS/DEMMV      DEMPAR
30      $          FORTY      DECK
40      $          PRMFL      C*,W,S,REQS/DEMPAR.O
50      $          REMOTE      P*,AC
60      $          REMOTE      $$,AC
70      C          DEMPAR FOR DODSIM
80      SUBROUTINE DEMPAR(IDPER,IP4,IP5)
90      COMMON/IGBUG/IGBUG
100     COMMON/ITIME/ITIME
110     COMMON/ITWEEK/ITWEEK
120     COMMON/ITMNTN/ITMNTN
130     COMMON/ITQTR/ITQTR
140     COMMON/ITYEAR/ITYEAR
150     COMMON/NITEM/NITEM
160     COMMON/NDENT/NDENT(1)
170     COMMON>IDEMND/IDEMND(1,24)
180     COMMON/IRETUR/IRETUR(1,24)
190     COMMON/IREQ/IREQ(1,24)
200     IF(IGBUG.NE.1) GO TO 25
210     IY=ITIME/ITYEAR +1
220     IQT=ITIME/ITQTR +1
230     ITW=(ITIME-(IY-1)*ITYEAR)/ITWEEK +1
240     WRITE(6,103)IY,IQT,ITW
250     103  FORMAT(12H DEMPAR-----,5X,8HYEAR NO.,13,5X,7HQTR NO.,13,5X,
260     1WO.,13)
270     25  CONTINUE
280
290     C          INCREMENT PERIOD COUNTERS
300     C
310     IDPER=IDPER+1
320     DO 100 N=1,NITEM
330     IQTY=IDEMND(N,IDPER)
340     IRET=IRETUR(N,IDPER)
350     IRQ=IREQ(N,IDPER)
360     IF(IGBUG.EQ.1)WRITE(6,8013)N,NDENT(N),IDPER,IQTY,IRET,IRQ
370     8013  FORMAT(4X,****DEMPAR--N=,15,NDENT=,15,IDPER=,15,
380     2      IDEMND=,15,IRETRN=,15,IREQ=,15)
390     IF(NDENT(N).LE.0) GO TO 100
400
410     C          GENERATE SERVICEABLE RETURNS, IF ANY
420     C
430     IF(IRET.LE.0)GO TO 30
440     IT=ITIME+ITMNTN
450     CALL ENTER(IT,4,N,IRET,0)
460     30  CONTINUE
470
480     C          REFLECT REQUISITION FOR ITEM N
490     C

```



DEMPAR (CONT)

2 6 3

```

500 IF(IQTV.LE.0) GO TO 100
510 ITOT=0
520 C
530 C OBTAIN A REQUISITION SIZE IR BY MONTE CARLO
540 C
550 50 R=RANDU(.2)
560 CALL GETREQ(R,IQTV,IR)
570 ITEMP=ITOT+IR
580 IR=IR
590 IF(ITEMP.LE.IQTV) GO TO 60
600 C
610 C LIMIT LAST REQUISITION SO THAT TOTAL DEMAND IN CF
620 C EQUALS IQTV.
630 C
640 IR=IQTV-ITOT
650 C
660 C DETERMINE ARRIVAL TIME FOR THIS REQUISITION
670 C
680 50 CONTINUE
690 IT=ITIME+RANDU(.2)*FLOAT(ITOTR)
700 IF(IGBUG.EQ.1)WRITE(6,8023)IT,N,R,IRQ,IR
710 8023 FORMAT(4X, '****DEMPAR--IT=',I10, ' N=',I4, ' R=',F5.3,
720 ' INITIAL REQ-SIZE=',I4, ' FINAL REQ-SIZE=',I4)
730 CALL ENTER(IT,1,N,IR,1)
740 ITOT=ITOT+IR
750 IF(ITOT.LT.IQTV) GO TO 50
760 C
770 C*****CREATE NEXT DEMPAR EVENT
780 C
790 100 CONTINUE
800 IT=ITIME+ITOTR
810 CALL ENTER(IT,12,IDPER,0,0)
820 RETURN
830 END
840 C
850 C
860 C
870 SUBROUTINE GETREQ(R,IQTV,IR)
880 C THIS ROUTINE DETERMINES A REQUISITION SIZE
890 C CORRESPONDING TO A CUM PROP. OF R.
900 C
910 DIMENSION IUCAT(8),CPROR(10,8),IRO(10,8)
920 DATA IUCAT/1,3,10,31,100,316,1000,3162/
930 DATA CPROR/10*1.,
940 & .46,.89,8*1.0,
950 & .27,.52,.65,.78,.86,.91,.92,.95,.96,1.0,
960 & .23,.53,.70,.78,.82,.90,.92,.97,.99,1.00,
970 & .06,.38,.60,.73,.81,.85,.89,.93,.98,1.00,
980 & .015,.23,.42,.56,.65,.70,.76,.92,.97,1.00,
990 & .012,.17,.31,.37,.48,.55,.60,.78,.87,1.00,
1000 & .001,.03,.32,.50,.60,.66,.86,.96,1.00,1.00/

```

```

1010 DATA IRG/10*1,
1020      1, 2, 3, 7*3,
1030      1, 2, 3, 4, 5, 6, 7, 8, 9, 10,
1040      1, 4, 6, 8, 10, 13, 15, 20, 25, 30,
1050      1, 5, 10, 15, 20, 25, 30, 40, 70, 100,
1060      1, 5, 10, 15, 20, 25, 30, 80, 150, 300,
1070      1, 5, 10, 15, 20, 25, 30, 80, 200, 600,
1080      1, 20, 40, 60, 80, 100, 200, 300, 600, 700/
1090 C
1100 C
1110 C ESTABLISH DEMAND RATE CATEGORY
1120 C
1130 DO 10 I=1,8
1140 IM=I
1150 IM=IUCAT(I)
1160 IF(IGTY.LE.M) GO TO 30
1170 10 CONTINUE
1180 C
1190 C DETERMINE REGQUISITION SIZE
1200 C
1210 30 CONTINUE
1220 DO 40 I=1,10
1230 IF(CPROB(I,IM).GE.R) GO TO 60
1240 40 CONTINUE
1250 60 CONTINUE
1260 C
1270 C SET REGQUISITION SIZE
1280 C
1290 IF(I.GT.1)GO TO 80
1300 IR=1
1310 RETURN
1320 80 CONTINUE
1330 IF(I.LT.10)GO TO 100
1340 IR=IRG(I,IM)
1350 RETURN
1360 100 CONTINUE
1370 DPROB=CPROB(I,IM)-CPROB(I-1,IM)
1380 RPROB=R-CPROB(I-1,IM)
1390 DRG=IRG(I,IM)-IRG(I-1,IM)
1400 IR=IRG(I-1,IM)+IFIX(RPROB*DRG/DPROB+.5)
1410 RETURN
1420 END
1430 *NDJOB

```



Subroutine: ENTER

Function:

This routine enters transactions on the Future Events List, and updates the associated pointer variables.

Description:

Subroutine ENTER places events on the Future Events List, and updates the associated pointer variables. These transactions are subsequently removed by subroutine REMOVE. See Volume I, Chapter IV for a discussion of these operations.

02-11-77 11.706

ENTER,  
P. 1 of 2

```

SUBROUTINE ENTER(KTIME,KTYPE,KESN,KQTY,KPRIOR)
C      THIS ROUTINE ENTERS EVENTS ON THE FUTURE EVENTS LIST
C      AND UPDATES THE CHAIN STRUCTURE
COMMON/IDBUG/IDBUG
COMMON/ITIME/ITIME
COMMON/NENTRY/NENTRY
COMMON/NEEMAX/NEEMAX
COMMON/NEIRST/NEIRST
COMMON/NELOC/NELOC
COMMON/NTIME/NTIME
COMMON/NORDET/NDDEPT(50)
COMMON/ILOC/ILOC(500)
COMMON/JESN/JESN(500)
COMMON/JPOINT/JPOINT(500)
COMMON/JPRIOR/JPRIOR(500)
COMMON/JQTY/JQTY(500)
COMMON/JTIME/JTIME(500)
COMMON/JTYPE/JTYPE(500)
C      BEGIN BY UPDATING COUNT OF ENTRIES IN FILE
NENTRY=NENTRY+1
C      IF THIS ENTRY EXCEEDS CAPACITY OF THE CHAIN, PRINT
C      ERROR MESSAGE AND QUIT
IF (NENTRY.GT.NEEMAX) GO TO 98
C      PLACE TRANSACTION IN FIRST AVAILABLE LOCATION
20 K=ILOC(NENTRY)
NELOC=K
JTIME(K)=KTIME
JTYPE(K)=KTYPE
JESN(K)=KESN
JQTY(K)=KQTY
JPRIOR(K)=KPRIOR
C      CHECK TO SEE IF THIS IS THE ONLY ENTRY ON THE LIST
IF (NENTRY.NE.1) GO TO 40
C      UPDATE LIST STATUS AND POINTER VARIABLES
NEIRST=K
NTIME=KTIME
JPOINT(K)=0
GO TO 100
C      DOES THE NEW TRANSACTION PRECEED ALL OTHER LIST ENTRIES?
40 IF (KTIME.GE.NTIME) GO TO 60
C      INSERT NEW TRANSACTION AS A FIRST LINK IN THE CHAIN
JTIME=KTIME
JPOINT(K)=NEIRST
NEIRST=K
GO TO 100
C      THE FOLLOWING STEPS SEARCH DOWN THE FILE AND
C      INSERTS THE TRANSACTION IN THE PROPER LOCATION
60 JJ=NEIRST
KJ=JPOINT(JJ)
C      IS JJ THE LAST RECORD ON THE CHAIN?
62 IF (KJ.EQ.0) GO TO 97
C      DOES THE NEW TRANSACTION PRECEED KJJ

```

ENTER  
p 2 of 2

02-11-77 10.706

```
IF (TIME .LT. JTIME(KJ)) GO TO 80
IJ=KJ
KJ=JPOINT(IJ)
GO TO 62
C      INSERT NEW TRANSACTION AS THE LAST LINK ON THE CHAIN
97  JPOINT(IJ)=K
    JPOINT(K)=0
    GO TO 100
C      INSERT NEW TRANSACTION ON THE CHAIN
80  JPOINT(IJ)=K
    JPOINT(K)=KJ
    GO TO 100
C      WRITE ERROR MESSAGE
90  WRITE(6,91)
91  FORMAT(1H,55HCAPACITY OF EE CHAIN EXCEEDED CHAIN LISTED ON NEXT P
    PAGE)
    WRITE(6,92)
92  FORMAT(1H,35X,65H      JTIME      JTYPE      JPOINT      JESN
    C JTY      JPRIO,Z)
    WRITE(6,93) (I,JTIME(I),JTYPE(I),JPOINT(I),JESN(I),JTY(I),I=1,NF
    PMAX)
93  FORMAT(1H,31X,14,4X,18,19,5X,15,3X,110,19,4X,12)
    RETURN
100  CONTINUE
    IF (IERR.NE.1) GO TO 25
    WRITE(6,8000) IERR,TIME,KTYPE,KESN,KJTY,PRIOR,K,NFIRST,NENTRY,N
    TIME
8000  FORMAT(2H ENTER,110,40X,810,17)
25  CONTINUE
    RETURN
END
```

Subroutine: ENTERB

Function:

This routine records backorders in the backorder file, and updates associated pointed variables.

Description:

This routine records backorders in the backorder file. Backorders are stored in link list form, with pointers from each recorded backorder to the oldest outstanding backorder for the associated item. In this link list, the highest priority, oldest backorder is stored first; that is, backorders are recorded on a first in first out basis within priority. See Volume I, Chapter V for variable definitions.

The variable NBOPT (N) defines the location of the oldest, highest priority backorder for item N. When new stock is received, this backorder will be the first requisition to be filled.

1 04-16-77 12.104

ENTER B

P. 1 of 2

```

C      SUBROUTINE ENTERB(N,IQTY,IPRI,JTIME)
C      THIS ROUTINE BACKORDERS REQUISITIONS FOR ITEM N
C      IQTY=QUANTITY PLACED ON BACKORDER
C      IPR =1  HIGH PRIORITY REQUISITION
C      IPRI=2  OTHERWISE
C      JTIME= CLOCK TIME REQ WAS RECEIVED
C      COMMON/NBMAX/NBMAX
C      COMMON/NLOCBK/NLOCBK
C      COMMON/NBOPT/NBOPT(50)
C      COMMON/IBACPT/IBACPT(200)
C      COMMON/IDFSNB/IDFSNB(200)
C      COMMON/ILOCBK/ILOCBK(200)
C      COMMON/IPRIOR/IPRIOR(200)
C      COMMON/IQTYB/IQTYB(200)
C      COMMON/ITMBAC/ITMBAC(200)
C      RESERVE A STORAGE LOCATION FOR THIS INFORMATION
C      IPT=ILOCBK(NLOCBK)
C      NLOCBK=NLOCBK+1
C      DID THIS REQUISITION CAUSE THE BACKORDER FILE TO OVERFLOW
C      IF(NLOCBK,GE,0)GO TO 20
C      WRITE ERROR MESSAGE
C      WRITE(6,91)
91  FORMAT(1H0,20X,53HERROR--BACKORDER FILE OVERFLOW,FILE DUMP ON NEXT
C  PAGE)
C      WRITE(6,82)
82  FORMAT(1H1,10X,23H**BACKORDER FILE DUMP**)
C      DO 83 K=1,NBMAX
83  WRITE(6,84) K,ITMBAC(K),IDFSNB(K),IPRIOR(K),IQTYB(K),IBACPT(K)
84  FORMAT(1H ,3X,7HREC NO=,I3,5X,7HITMBAC=,I7,5X,7HIDFSNB=,I10,5X,7HI
C      CPRIOR=,I1,5X,6HIQTYB=,I7,5X,7HIBACPT=,I7)
C      RETURN
C      RECORD QUANTITY,PRIORITY,FSN ID,AND TIME DATA FOR THIS BO REQ
20  ITMBAC(IPT)=JTIME
C      IDFSNB(IPT)=N
C      IPRIOR(IPT)=IPRI
C      IQTYB(IPT)=IQTY
C      ARE ANY OTHER BACKORDERS OUTSTANDING ON ITEM N
C      IF(NBOPT(N),GT,0) GO TO 40
C      RECORD POINTER DATA
C      NBOPT(N)=IPT
C      IBACPT(IPT)=0
C      RETURN
C      IS THE NEW BO A PRIORITY 1 REQUISITION
40  IF(IPRI,EQ,1) GO TO 60
C      NOTE-- NEW LOW PRIORITY BACKORDERS ARE INSERTED LAST ON THE
C      BACKORDER CHAIN. THE REMAINING STEPS IN THIS PORTION
C      OF THE SUBROUTINE ACCOMPLISH THIS OBJECTIVE
C      SET JPT EQUAL TO THE FILE LOCATION NO OF THE FIRST BACKORDERED
C      REQUISITION IN THE CHAIN
C      JPT=NBOPT(N)
C      IS JPT THE LAST LINK IN THE CHAIN
49  IF(IBACPT(JPT),EQ,0) GO TO 50
```

ENTER B,  
p. 2

```
KPT=IBACPT(JPT)
JPT=KPT
GO TO 49
C   RECORD NEW POINTERS
50 IBACPT(JPT)=IPT
   IBACPT(IPT)=0
   RETURN
C   SET JPT EQUAL TO LOCATION NO OF FIRST BO ON CHAIN
60 JPT=NBOPT(N)
C   IS BACKORDER JPT A HIGH PRI BO
61 IF(IPRIOR(JPT).NE.1) GO TO 80
C   IS JPT THE LAST BACKORDER ON THE CHAIN
   IF(IBACPT(JPT).EQ.0) GO TO 62
   KPT=JPT
   JPT=IBACPT(KPT)
   GO TO 61
C   INSERT NEW BO AS LAST LINK ON CHAIN
62 IBACPT(JPT)=IPT
   IBACPT(IPT)=0
   RETURN
C   IS JPT THE ONLY BO ON CHAIN
80 IF(JPT.NE.NBOPT(N)) GO TO 81
C   INSERT NEW BO AS FIRST LINK ON CHAIN
   NBOPT(N)=IPT
   IBACPT(IPT)=JPT
   RETURN
C   INSERT NEW BO AS LINK BETWEEN KPT AND JPT
81 IBACPT(KPT)=IPT
   IBACPT(IPT)=JPT
   RETURN
END
```



Subroutine:    FILLBO

Function:

This routine is called to initiate shipping actions to fill outstanding backorders.

Description:

Subroutine FILLBO (N) is called to initiate shipping actions to fill outstanding backorders for item N. The routine assumes that backordered requisitions are filled using a first in first out, by priority, issue rule. If on hand assets are insufficient to completely fill a given requisition, partial shipments are initiated. Reduced shipments to partially fulfill several outstanding backorders are not permitted in this routine.

When FILLBO is called, it tests if the highest priority outstanding requisition may be filled completely from on hand stock. If so, and if this shipment will not take on hand stock below the support level, the requisition is removed from the backorder list, and a shipment for the requisition quantity is initiated. If the backorder is low priority (that is, code 2), shipments will be made until on hand stocks just equal the support level ISUL (N) for item N. For high priority requisitions, shipments are made until on hand stock is reduced to zero or until all high priority requisitions are filled, whichever occurs first.

FILLBO,  
p. 1 of 2

```

SUBROUTINE FILLBO(N)
COMMON/IDBUG/IDBUG
COMMON/NBOPT/NBOPT(50)
COMMON/INVACT/INVACT(50)
COMMON/IQTYB/IQTYB(200)
COMMON/ISUL/ISUL(50)
COMMON/IPRIOR/IPRIOR(200)
COMMON/ISHIPT/ISHIPT(30,3)
COMMON/NBOTU/NBOTU(50)
COMMON/ISHIPT/ISHIPT(30,3)
COMMON/IBACPT/IBACPT(200)
COMMON/NLOCBK/NLOCBK
COMMON/ILOCBK/ILOCBK(200)
25 IF(NBOPT(N).LE.0) RETURN
   IF(IDBUG.NE.1) GO TO 27
   I=NBOPT(N)
   WRITE(6,990)N,INVACT(N),IQTYB(I),IPRIOR(I),I
990  FORMAT(' ****FILLBO--ITEM=',I5,' OH=',I5,' IQTYB=',I5,
&        ' IPRIOR=',I5,' IPT=',I5)
27 CONTINUE
C   SET IPT EQUAL TO THE POINTER NUMBER OF THE OLDEST,HIGHEST
C   PRIORITY REQUISITION FOR ITEM N ON BACKORDER STATUS.
IPT=NBOPT(N)
IF(INVACT(N).LE.0)RETURN
**** NOTE ****
C   (A) THIS ROUTINE ASSUMES BO REQUISITIONS ARE FILLED USING
C   A FIFO,BY PRIORITY,ISSUE RULE
C   (B) IF ON-HAND ASSETS ARE INSUFFICIENT TO COMPLETELY FILL A
C   GIVEN REQUISITION,PARTIAL SHIPMENTS ARE INITIATED.
C   (C) REDUCED SHIPMENTS TO PARTIALLY FULFILL SEVERAL
C   OUTSTANDING BACKORDERS ARE NOT PERMITTED IN THIS ROUTINE
C
C   SET ITEST EQUAL TO THE REMAINING ON-HAND INVENTORY,
C   IF THE REQUISITION WAS TO BE COMPLETELY FILLED
ITEST=INVACT(N)-IQTYB(IPT)
C   IS ITEST ABOVE THE SUPPORT LEVEL
IF(ITEST.GT.ISUL(N)) GO TO 80
C   IS THIS A PRIORITY 1 REQUISITION
IF(IPRIOR(IPT).NE.1) GO TO 60
C   CAN THE REQ BE COMPLETELY SATISFIED FROM ON HAND STOCK
IF(INVACT(N).GE.IQTYB(IPT)) GO TO 80
C   SHIP ALL REMAINING ON-HAND STOCK IN PARTIAL FULFILLMENT
C   OF THIS REQUISITION
IQTYS=INVACT(N)
C   UPDATE PRIORITY 1 BACKORDER STATISTICS
JQTYS=JQTYS+IQTYS
CALL CUM(ISHIPT,IQTYS,N)
GO TO 65
C   ARE ON-HAND ASSETS ABOVE THE SUPPORT LEVEL
C   IF(INVACT(N).GE.ISUL(N)) GO TO 70
C   SHIP DOWN TO THE SUPPORT LEVEL
IQTYS=INVACT(N)-ISUL(N)

```



04-16-77 12.096

FILLBO, P. 2

```
C      UPDATE STOCK STATUS RECORDS TO REFLECT THE PARTIAL SHIPMENT
65  INVACT(N)=INVACT(N)-IQTYS
    NBOTU(N)=NBOTU(N)-IQTYS
    IQTYB(IPT)=IQTYB(IPT)-IQTYS
C      UPDATE GROSS PERFORMANCE STATISTICS
    JQTYB=-IQTYS
    CALL CUM(ISHIPT,IQTYB,N)
C      AT THIS POINT, NO FURTHER SHIPMENTS SHOULD BE POSSIBLE, SINCE
C      HIGH PRIORITY REQUISITIONS ARE PROCESSED FIRST
70  RETURN
C      SHIP TO FILL THE ENTIRE REQUISITION
80  IQTYS=IQTYB(IPT)
C      UPDATE STOCK STATUS RECORDS
    INVACT(N)=INVACT(N)-IQTYS
    NBOTU(N)=NBOTU(N)-IQTYS
    JQTYB=-IQTYS
    CALL CUM(ISHIPT,IQTYB,N)
C      IS THIS A PRIORITY 1 REQ.
    IF(IPRIOR(IPT).NE.1) GO TO 100
C      UPDATE PRIORITY 1 STATISTICS
    CALL CUM(ISHIPT,IQTYB,N)
C      REMOVE REQUISITION FROM THE BACKORDER FILE
100 NBOTU(N)=IBACPT(IPT)
    NLOCBK=NLOCBK+1
    ILOCBK(NLOCBK)=IPT
C      RETURN TO BEGINNING OF ROUTINE TO SEE IF ANY MORE BO
C      NEED TO BE PROCESSED.
    GO TO 25
END
```

Subroutine: FOR576

Function:

This routine updates forecasted demand rates and standard deviation estimates based on information recorded in the History File.

Description:

This routine uses an eight quarter moving average to update forecasts of the net annual demand rate  $ADR(N)$ , the MAD of quarterly unit demand  $QMAD$ , and average requisition size  $REQSIZ(N)$  associated with item  $N$ . The estimate of the standard deviation of lead time demand  $RSIGLT(N)$  is then updated using the formula

$$RSIGLT(N) = 0.5945 * QMAD * (0.82375 + 0.42625 * RLT)$$

where  $RLT$  denotes the total of the administrative and production leadtimes for item  $N$ .

To avoid numerical problems in other routines, FOR576 compares the computed values to the following bounds, and, if the bound is violated, FOR576 resets the variable equal to the associated bound.

$ADR(N)$	$\geq$	0.0
$QMAD$	$\geq$	.01
$RSIGLT(N)$	$\geq$	.01
$REQSIZ(N)$	$\geq$	1.0

```

20      $      IDENT    WP0287,ADDSC-CALLAHAN
30      $      FORTY    DECK
40      $      PRMFL    C*,W,S,REQS/FOR576.0
50      $      REMOTE    P*,AC
60      $      REMOTE    $$,AC
70      SUBROUTINE FOR576(N)
80      COMMON/IFBUG/IFBUG
90      COMMON/ITIME/ITIME
100     COMMON/ITQTR/ITQTR
110     COMMON/NDEMAC/NDEMAC(1)
120     COMMON/NRETAC/NRETAC(1)
130     COMMON/NREQAC/NREQAC(1)
140     COMMON/NDEMND/NDEMND(1,24)
150     COMMON/REQSIZ/REQSIZ(1)
160     COMMON/NRETUR/NRETUR(1,24)
170     COMMON/NREQ/NREQ(1,24)
180     COMMON/ADR/ADR(1)
190     COMMON/RSIGLT/RSIGLT(1)
200     COMMON/NDENT/NDENT(1)
210     COMMON/LTADM/LTADM(1)
220     COMMON/LTPROD/LTPROD(1)
230     COMMON/UCOST/UCOST(1)
240     COMMON/IDBUG/IDBUG
250     COMMON/ICDFOR/ICDFOR
260     COMMON/ICDSIG/ICDSIG
270     COMMON/SRFOR/SRFOR,SRPLT,GDFOR
280     LW=6
290     NLOOP=24
300     IDUM=0
310     IFUM=0
320     IRUM=0
330     KK=NDENT(N)
340     IF(KK.GT.8)KK=8
350     KL=KK-1
360     DO 1 I=1,KL
370     IDUM=IDUM + NDEMND(N,I)
380     IFUM=IFUM + NREQ(N,I)
390     1 IRUM=IRUM + NRETUR(N,I)
400     C
410     IT=MOD(ITIME,ITQTR)
420     R=FLOAT(IT)/FLOAT(ITQTR)
430     RM=1.-R
440     DUM=R*FLOAT(NDEMAC(N))+FLOAT(IDUM)+RM*FLOAT(NDEMND(N,KK))
450     FUM=R*FLOAT(NREQAC(N))+FLOAT(IFUM)+RM*FLOAT(NREQ(N,KK))
460     RUM=R*FLOAT(NRETAC(N))+FLOAT(IRUM)+RM*FLOAT(NRETUR(N,KK))

```

```

470      C
480      C
490      *
500      *      COMPUTE LEVELS BASED ON NET DEMANDS, WHERE NET IS
510      *      DEMAND MINUS SERVICEABLE RETURNS FOR THE PAST
520      *      MONTHS,
530      *      RETURNS ARE ADDITIONS TO ON-HAND ASSETS.
540      *
550      FOR=DUM-RUM
560      IF(FOR.LE.0.)GO TO 1000
570      FORCST=FOR/FLOAT(KK)
580      900  ADR(N)=FORCST*4.
590      C
600      C      COMPUTE MAD OF QUARTERLY DEMAND
610      C
620      QMAD=0.
630      FORCST=DUM/FLOAT(KK)
640      DO 20 I=1,KK
650      ABSDEV=ABS(FLOAT(NDEMND(N,I))-FORCST)
660      20    QMAD=QMAD+ABSDEV
670      QMAD=QMAD/FLOAT(KK)
680      IF(QMAD.LT. 0.01) QMAD=0.01
690      C
700      C      COMPUTE STANDARD DEVIATION OF LEADTIME DEMAND
710      C
720      RLT=FLOAT(LTADM(N)+LTPROD(N))
730      RSIGLT(N)=0.5945*QMAD*(0.82375+0.42625*RLT)
740      IF(RSIGLT(N).LT. 0.01) RSIGLT(N)= 0.01
750      C

```

```

760      C          COMPUTE AVERAGE REQUISITION SIZE
770      C
775      IF(IFUM.LT.1)IFUM=1
780      R=FLOAT(IDUM)/FLOAT(IFUM)
790      IF(R.LT.1.)R=1.
800      REQSIZ(N)=R
810      2000 IF(IFBUG.NE.1) RETURN
820      WRITE(LW,100)
830      WRITE(LW,200) N,NDENT(N),NLOOP,ICDFOR,ICDSIG,LTADM(N),LTPROD
840      WRITE(LW,300)
850      WRITE(LW,200)NDEMAC(N),(NDEMND(N,J),J=1,KK)
860      WRITE(LW,200)NRETAC(N),(NRETUR(N,J),J=1,KK)
870      WRITE(LW,200)NREQAC(N),(NREQ(N,J),J=1,KK)
880      WRITE(LW,400)
890      WRITE(LW,500) FORCST,ADR(N),REQSIZ(N),UCOST(N),QMAD,RSIGLT
900      100  FORMAT(1H,4X, '****FOR576--N,NDENT,NLOOP,ICDFOR,ICDSIG',
910      &      LTADM,LTPROD')
920      200  FORMAT(1H,4X,12I7/12I7)
930      300  FORMAT(1H,9X, 'DEMAND, RETURNS, AND FREQ',
940      &      IN CURRENT HISTORY FILE')
950      400  FORMAT(1H, '      FORCST      ADR      AVE-REQ      UCOST',
960      &      QMAD      RSIGLT')
970      500  FORMAT(1H,6F10.4)
980      RETURN
990      1000 RSIGLT(N)=.5
1000      ADR(N)=0.0
1010      IF(IFBUG.NE.1) RETURN
1020      GO TO 2000
1030      END
1040      $      ENDJOB

```

Subroutine: FORUPD

Function:

This routine slides the demand history files for all items at the end of each quarter. It also resets the demand accumulator variables.

Description:

Subroutine FORUPD first increments the counter NDENT(N) for each item N. This variable counts the number of periods that item N has been in the inventory system.

The routine then slides the history values to the next oldest time slot. Variables affected are the NDEMND, number of units demanded per quarter, NRETUR, the number of serviceable returns, and NREQ, the number of requisitions submitted. The oldest quarter of data is dropped. The accumulator variables NDEMAC(N), NREQAC(N), and NRETAC(N) are then reset to zero. These variables are used to record the cumulative demand activity that occurs within the current quarter.

Finally, FORUPD places a new type 9 event on the Future Events List. This causes FORUPD to be called again IDFOR time units in the future.



```

20  $      IDENT  WP#287,ADDSC-CALLAHAN
30  $      FORTY  DECK
40  $      PRMFL  C*,W,S,REQS/FORUPD.O
50  $      REMOTE  P*,AC
60  $      REMOTE  $$,AC
70      SUBROUTINE FORUPD
80  C      THIS ROUTINE SLIDES THE DEMAND HISTORY FILES FOR ALL ITEM
90  C      THE END OF EACH FORECAST INTERVAL, RESETS IDAY, AND ZERO
100 C      THE DEMAND ACCUMULATORS
110      COMMON/ITFOR/ITFOR,IDFOR
120      COMMON/NITEM/NITEM
130      COMMON/NDEMND/NDEMND(1,24)
140      COMMON/NRETUR/NRETUR(1,24)
150      COMMON/NREQ/NREQ(1,24)
160      COMMON/NDEMAC/NDEMAC(1)
170      COMMON/NRETAC/NRETAC(1)
180      COMMON/NREQAC/NREQAC(1)
190      COMMON/NDENT/NDENT(1)
200      N=1
210  C      HAS ITEM N ENTERED THE SYSTEM YET
220      5  CONTINUE
230      NDENT(N)=NDENT(N)+1
240      IF(NDENT(N).GE.0) GO TO 20
250      GO TO 25
260  C      *** NOTE ***
270  C      BY CONVENTION NDENT(N) IS NEGATIVE UNTIL THE ITEM ENTERS
280  C      THE INVENTORY MANAGEMENT SYSTEM
290  C
300  C      SLIDE THE DEMAND HISTORY FILES FOR ALL ITEMS
310      20 CONTINUE
320      KK=8
330      KP=KK+1
340      KL=KK-1
350      DO 21 I=1,KL
360      IS1= KP-I
370      IS2= KK-I
380      NDEMND(N,IS1)=NDEMND(N,IS2)
390      NRETUR(N,IS1)=NRETUR(N,IS2)
400      NREQ(N,IS1)=NREQ(N,IS2)
410      21  CONTINUE
420      NREQ(N,1)=NREQAC(N)
430      NREQAC(N)=0
440      NRETUR(N,1)=NRETAC(N)
450      NRETAC(N)=0
460      NDEMND(N,1)=NDEMAC(N)
470      NDEMAC(N)=0
480  C      HAVE ALL ITEMS BEEN PROCESSED

```

FORUPD (CONT)

2 of 2

```
490      25 IF(N.GE.NITEM) GO TO 26
500          N=N+1
510          GO TO 5
520      26 CONTINUE
530      C      CREATE EVENT TO TRIGGER NEXT UPDATE
540          ITFOR=ITFOR+IDFOR
550          CALL ENTER(ITFOR,9,0,0,0)
560          RETURN
570          END
580      S      ENDJOB
```



Subroutine: GP

Function:

This routine provides a X-Y plot of the vectors provided as calling parameters. It is used by subroutine PLOTR to provide four plots of inventory characteristics as a function of time.

Description:

This routine automatically determines appropriate values for maximum and minimum of each plot axis. Definitions of each of the calling parameters are provided on page 1 of the program listing, and will not be discussed further here.

GP  
p. 1 of 3

```

SUBROUTINE GP(X,Y,L,S,M,N,W,LN,A,PLOT)
C**
C** CONTROL
C**
C
C** CALL GP (X, Y, L, S, M, W, LN, A, PLOT)
C**
C** WHERE
C**      X = ARRAY OF INDEPENDENT VALUES, DIMENSIONED X(M).
C**      Y = ARRAY OF SETS OF DEPENDENT VALUES, DIMENSIONED Y(M,N).
C**      L = NUMBER OF LINES TO BE SKIPPED BEFORE DISPLAY.
C**      S = NUMBER OF SPACES FROM THE LEFT SIDE OF PAGE TO
C**          BE SKIPPED BEFORE DISPLAY.
C**      M = NUMBER OF POINTS IN EACH SET.
C**      N = NUMBER OF SETS OF POINTS.
C**      W = WIDTH OF DISPLAY IN PRINT SPACES.
C**      LN = LENGTH OF DISPLAY IN PRINT LINES.
C**      A = ARRAY OF SINGLE CHARACTERS, DIMENSIONED A(N), TO
C**          REPRESENT THE TREND FOR EACH SET (EX., DATA A/1HA,
C**          1HB,...,ETC.)
C**      PLOT = ARRAY OF SINGLE CHARACTERS GENERATED BY GP TO
C**          DISPLAY TRENDS, DIMENSIONED PLOT (LN,W).
C**
C**      INTEGER S, W, W1
C
C      DIMENSION X(M), Y(M,N), A(N), PLOT(LN,W)
C
C      DATA BLANK/1H /, EDGE/1H*/
C      DATA ORD/1H /, ABSIS/1H-/
C
C** CHECK MAXIMUM WIDTH AND LENGTH REQUESTED AND
C** EXIT IF NOT CORRECT
C**
      IF (S+W .GT. 131) GO TO 900
      IF (L+LN .GT. 58) GO TO 800
C
C** FIND MINIMUM AND MAXIMUM OF X AND Y
C**
      XMAX=X(1)
      XMIN=X(1)
C
      DO 10 I=2,M
      IF (X(I) .GT. XMAX) XMAX=X(I)
      IF (X(I) .LT. XMIN) XMIN=X(I)
      10
      YMAX=Y(1,1)
      YMIN=Y(1,1)
C
      DO 20 I=1,M
      DO 20 J=1,N
      IF (Y(I,J) .GT. YMAX) YMAX=Y(I,J)

```

GP  
P.2 of 3

```
20 IF (Y(I,J) .LT. YMIN) YMIN=Y(I,J)
C
C
C*****
C
C      SET ORIGIN AT (0.,0.)
C
C      YMIN=0,
C      XMIN=0,
C
C      BEGIN ON NEW PAGE
C
C      WRITE(5,610)
610 FORMAT(1H1)
C*****
C
C**   COMPUTE SCALE FACTOR -- P FOR X, Q FOR Y
C**
C      P=FLOAT(W-1)/(YMAX-XMIN)
C      Q=FLOAT(LN-1)/(YMAX-YMIN)
C
C**   BLANK PLOT ARRAY
C**
C      DO 30 I=1,W
C      DO 30 J=1,LN
30   PLOT(J,I)=BLANK
C
C**   CONSTRUCT BORDER OF DISPLAY
C**
C      DO 40 J=1,LN
C      I=1
C      PLOT(J,I)=EDGE
C      I=W
40   PLOT(J,I)=EDGE
C
C      W1=W-1
C      DO 50 I=2,W1
C      J=1
C      PLOT(J,I)=EDGE
C      J=LN
50   PLOT(J,I)=EDGE
C
C**   COMPUTE SUBSCRIPTS AND INSERT TREND CHARACTER IN
C**   PLOT ARRAY
C**
C      DO 60 I=1,M
C      DO 60 J=1,N
C      I1=1+INT(0.5+P*(X(I)-XMIN))
C      J1=LN-INT(0.5+Q*(Y(I,J)-YMIN))
60   PLOT(J1,I1)=A(J)
C
C**   SKIP L LINES BEFORE BEGINNING DISPLAY PRINTING
```

GP

p. 3 of 3

```
C      DO 70 K=1,L
70     WRITE (6,600)
600    FORMAT (1H )
C
C**   WRITE OUT PLOT ARRAY, SKIPPING S SPACES BEFORE PRINTING
C**   EACH LINE OF DISPLAY
C**
      DO 80 J=1, LN
80     WRITE(5,601) (BLANK,K=1,S), (PLOT(J,I),I=1,W)
601    FORMAT (132A1)
      WRITE (6,602) XMIN,XMAX,YMIN,YMAX
602    FORMAT (1H0,5X,6HXMIN =E16,8,10X,6HXMAX =E16,8,10X,
X      6HYMIN =E16,8,10X,6HYMAX =E16,8)
      RETURN
C**
C**   ERROR MESSAGES BEFORE TERMINATION
C**
800    WRITE (6,603) L, LN
603    FORMAT (30HAL+LN IS GREATER THAN 58   L =I3,5X,4HLN =I3)
900    WRITE (6,604) S, W
604    FORMAT (30HAS+W IS GREATER THAN 131   S =I3,5X,3HW =I3)
      STOP
      END
```

Subroutine: GUIDE

Function:

This routine establishes guidelines for levels computations to be performed by subroutine LEVELN.

Description:

This routine establishes guidelines for levels computations based on a comparison of current obligations and budget authorizations for the current budget period. However, no buys are permitted after the obligation ceiling for a given budget interval has been reached.

Methodology to be used in establishing buy guidelines is determined by the code ICDGID provided as input to the simulation.

At the end of this event, GUIDE places a new type 7 event on the Future Events List.

## SUBROUTINE GUIDE

```

C   THIS ROUTINE ESTABLISHES GUIDELINES FOR LEVELS COMPUTATIONS
C   ACCORDING TO POLICY STATED IN AFLCM 57-6, HOWEVER NO BUYS ARE
C   PERMITTED AFTER THE OBLIGATION CEILING FOR A GIVEN BUDGET
C   INTERVAL IS REACHED.
COMMON/IGRUG/IGRUG
COMMON/IDDIV/IDDIV
COMMON/IOBLIG/IOBLIG
COMMON/ITDIV/ITDIV
COMMON/ITHQ/ITHQ
COMMON/ITIME/ITIME
COMMON/ITYEAR/ITYEAR
COMMON/MAXBUY/MAXBUY
COMMON/NBPER/NBPER
COMMON/GSLF/GSLF
COMMON/GRLF/GRLF
COMMON/GTLF/GTLF
COMMON/GUIDI/ICDGUID,NPH,NPOLCY,IDJAXR,IDJAXS,SHORT(10)
COMMON/IBAUTH/IBAUTH(12)
COMMON/GEOQ/GEOQ(3)
C   DO CURRENT OBLIGATIONS EXCEED THE CEILING
IF(IOBLIG,LE,IBAUTH(NBPER))GO TO 11
IF(MAXBUY,LE,?) GO TO 20
MAXBUY=0
GO TO 20
11 CONTINUE
MAXBUY=9999999
20 CONTINUE
IF(IGRUG,NB,1) GO TO 30
R=FLOAT(ITIME)/FLOAT(ITYEAR)
WRITE(6,8000)ITIME,NBPER,IOBLIG,IBAUTH(NBPER),R,MAXBUY
8000 FORMAT(7H 3ID576,I10,5H---,6HNBPB=,15,5X,12HOBLIGATIONS=,I10,5X
C,11HAUTHORIZED=,I10,5X,5HYEAR=,F6.3,5X,8HMAXBUY=,19)
30 CONTINUE
IF(ICDGUID,EQ,1) GO TO 50
IF(ICDGUID,EQ,2) GO TO 40
GEOQ(1)=3.
GEOQ(2)=6.
GEOQ(3)=12.
GSLF=1.
GSULF=0.
GTLF=24.
GRLF=12.
GO TO 50
40 CONTINUE
CALL A22JAX
50 CONTINUE
C   COMPUTE TIME FOR NEXT GUIDELINE REVIEW
ITDIV=ITDIV+IDDIV
C   IF NEXT REVIEW TIME PRECEEDS NEXT BUDGET REVISION
C   PLACE REVIEW EVENT ON FB LIST
IF(ITDIV,GE,ITHQ) GO TO 13

```

01 12-08-76 20.417

CALL ENTER(ITDIV,7,0,0,0)  
13 CONTINUE  
RETURN  
END



Subroutine: INBUDG1

Function:

This routine performs initialization functions required in simulating buy guidelines events.

Description:

The subroutine INBUDG1 sets authorized and projected obligation ceilings. The routine also initializes obligation and period counters, and places the initial budget review event on the Future Events List.

The routine sets the authorized budget ceilings equal to the total dollar demand to be generated in the corresponding budget interval. That is, it sets the budget authorization equal to the dollar value of unit demand in the array IDEMND; this array drives the simulated demand activity for the simulation.

Finally, routine INBUDG1 places a type 8 event on the Future Events List.

11 12-08-76 19.875

INBUDG1

p.1 of 2

```

C      SUBROUTINE INBDG1
C      THIS ROUTINE SETS AUTHORIZED AND PROJECTED OBLIGATIONS CEILINGS
C      EQUAL TO THE TOTAL DOLLAR DEMAND OBSERVED IN THE CORRESPONDING
C      BUDGET INTERVAL. THE ROUTINE ALSO INITIALIZES OBLIGATION AND
C      PERIOD COUNTERS AND PLACES THE BUDGET REVIEW EVENT ON THE FEL.
      DIMENSION TOTAL(30)
      COMMON/BPER/BPER
      COMMON/IOBLIG/IOBLIG
      COMMON/NITEM/NITEM
      COMMON/INQTR/INQTR
      COMMON/NBPER/NBPER
      COMMON/ITHQ/ITHQ
      COMMON/IDEMND/IDEMND(50,81)
      COMMON/UCOST/UCOST(50)
      COMMON/IBAUTH/IBAUTH(12)
      COMMON/IBPROJ/IBPROJ(12)
C
C      COMPUTE ACTUAL $/QTR DEMAND
C
      ISW=1
      IF(ISW.EQ.1)GO TO 200
      DO 30 I=1,27
      TOTAL(I)=0.
      SUM=0.
      DO 13 N=1,NITEM
      IF(IDEMND(N,I).GE.999999) GO TO 13
      SUM=SUM+FLOAT(IDEMND(N,I))*UCOST(N)
13  CONTINUE
      TOTAL(I)=SUM
30  CONTINUE
C
C      SET AUTHORIZED BUDGET EQUAL TO ACTUAL DEMAND
C
      DO 50 I=1,7
      K=4*I-3
      SUBTOT=TOTAL(K)+TOTAL(K+1)+TOTAL(K+2)+TOTAL(K+3)
      IBAUTH(I)=BPER*SUBTOT
      IBPROJ(I)=SUBTOT
50  CONTINUE
      WRITE(6,8000)(I,TOTAL(I),I=1,27)
8000 FORMAT(///20X,6HQTR NO.8X,7HSDemand///30(I26,F15.2/))
      WRITE(6,8010)(K,IBPROJ(K),IBAUTH(K),K=1,7)
8010 FORMAT(///20X,6H YR NO.8X,7H$ACTUAL.10X,5H$AUTH///10(I26.2I15/))
      GO TO 500
200 CONTINUE
      DO 25 I=1,7
      IBAUTH(I)=99999999.
250 IBPROJ(I)=99999999.
500 CONTINUE
C      ENTER BUDGET REVISION EVENT ON FE LIST
      CALL ENTER(ITHQ,8,1,0,0)
C      INITIALIZE BUDGET INTERVAL COUNTER
```

12-08-76 19.875

NRPER=0  
RETURN  
END

INBUDG1

P. 2 of 2

Subroutine: INFEL

Function:

This routine initializes the Future Events List to an empty status.

Description:

Subroutine INFEL initializes the Future Events List. Subsequently, Subroutines ENTER and REMOVE update this list. See Volume I, Chapter IV, for a detailed discussion of these activities.

INFEL,  
P. 1 of 1

02-11-77 10.687

SUBROUTINE INFEL

C THIS ROUTINE INITIALIZES THE FUTURE EVENTS

C LIST TO AN EMPTY STATUS

COMMON/NENTRY/NENTRY

COMMON/NFEMAX/NFEMAX

COMMON/NTIME/NTIME

COMMON/ILOCFZ/ILOCFZ(500)

NFEMAX=500

NENTRY=0

NTIME=9999999

DO 1 I=1,NFEMAX

1 ILOCFF(I)=1

DETFZD

END

Subroutine: INITIAL

Function:

This routine sets the values of critical timing variables and initializes the Future Events List.

Description:

First, this routine calls Subroutine INFEL to initialize the Future Events List. Next, major parameters for the Backorder File are set, and the Backorder File is initialized.

Major timing variables are then set assuming that there are 100 time units in each simulated day. At present, Subroutine INITIAL assumes that there are 7 days per week, 4 weeks per month, 3 months per quarter, and 4 quarters in each year.

Subroutine INITIAL then sets the simulation clock and statistics collection variables; specifically, it sets:

ITIME = 0.

ITINV = 1.

INITAL then sets other significant timing variables discussed in Chapter IV, Volume I.

Finally, INITIAL places transactions for event types 3, 5, 6, 10, 11, 12, and 13 on the Future Events List, provided these events are to be simulated in the current simulation run.

INITAL

P 1 of 3

```
20  $  IDENT  WP0287,ADDSC-CALLAHAN
30  $  FORTY  DECK
40  $  PRMFL  C*,W,S,REQS/INITAL.O
50  $  REMOTE  P*,AC
60  $  REMOTE  $$,AC
70  SUBROUTINE  INITAL
80  C  THIS ROUTINE
90  C  INITIALIZES THE FUTURE EVENTS LIST.
100 C
110 COMMON/IDBUG/IDBUG,IEBUG,IFBUG,IGBUG,IHBUG
120 COMMON/ITRACE/ITRACE,ISTRAC
130 COMMON/IDDIV/IDDIV
140 COMMON/IDLEVL/IDLEVL
150 COMMON/IDSTAT/IDSTAT
160 COMMON/IDTHQ/IDTHQ
170 COMMON/IKDEM/IKDEM
180 COMMON/INQTR/INQTR
190 COMMON/IQTRND/IQTRND
200 COMMON/ISTOCK/ISTOCK,IDSTOC
210 COMMON/ISTOP/ISTOP
220 COMMON/ISTAT/ISTAT
230 COMMON/ITCANB/ITCANB,IDCANB
240 COMMON/ITDAY/ITDAY
250 COMMON/ITDIV/ITDIV
260 COMMON/ITFOR/ITFOR,IDFOR
270 COMMON/ITHQ/ITHQ
280 COMMON/ITIME/ITIME
290 COMMON/ITINV/ITINV
300 COMMON/ITLEV/ITLEV
310 COMMON/ITMNT/ITMNT
320 COMMON/ITQTR/ITQTR
330 COMMON/ITWEEK/ITWEEK
340 COMMON/ITYEAR/ITYEAR
350 COMMON/MBODAY/MBODAY
360 COMMON/NBMAX/NBMAX
370 COMMON/NENTRY/NENTRY
380 COMMON/NFEMAX/NFEMAX
390 COMMON/NFIRST/NFIRST
400 COMMON/NITEM/NITEM
410 COMMON/NLOC/NLOC
420 COMMON/NLOCBK/NLOCBK
430 COMMON/NTIME/NTIME
440 COMMON/RAND/IX,IY
450 COMMON/ILOCBK/ILOCBK(200)
460 C
```



1-2 of 3

```
470 C      INITIALIZE THE FUTURE EVENTS LIST
480 C
490      NFEMAX=500
500      CALL INFEL
510 C
520 C      SET PARAMETERS FOR BACKORDER FILE
530 C
540      NBMAX=100
550      NLOCBK=NBMAX
560      DO 10 I=1,NBMAX
570 10 ILOCBK(I)=NBMAX+1-I
580 C      SET TIMING VARIABLES BASED ON 100 TIME UNITS PER DAY
590 C      7 DAYS/WEEK, 4 WEEKS/MONTH, 4 QUARTERS/YEAR
600      ITDAY=100
610      ITWEEK=7*ITDAY
620      ITMNTN=4*ITWEEK
630      ITQTR=3*ITMNTN
640      ITYEAR=4*ITQTR
650 C      SET TIMING VARIABLES FOR MANAGEMENT AND DATA COLLECTION
660 C      CURRENT SIMULATION CLOCK TIME
670      ITIME=0
680 C      CURRENT STATISTICS COLLECTION INTERVAL
690      ITINV=1
700 C      END OF CURRENT QUARTER
710      IQTRND=ITQTR
720 C      TIME OF FIRST HQ USAF BUDGET AUTHORIZATION
730      ITHQ=10
740 C      TIME BETWEEN HQ USAF BUDGET REVISIONS
750      IDTHQ=4*ITQTR
760 C      TIME OF FIRST DIVISION LEVEL REVIEW
770      ITDIV=20
780 C      TIME BETWEEN DIVISION LEVEL REVIEWS
790      IDDIV=ITMNTN
800 C      TIME OF FIRST STOCK LEVEL COMPUTATION
810      ITLEV=30
820 C      TIME BETWEEN STOCK LEVEL COMPUTATIONS
830      IDLEV=2*ITWEEK
840 C      TIME OF FIRST STOCK STATUS REVIEW
850      ISTOCK=40
860 C      TIME BETWEEN STOCK STATUS REVIEWS
870      IDSTOC=2*ITWEEK
880 C      TIME TO ACTIVATE STATISTICS COLLECTION ROUTINE
890      ISTAT=ITWEEK-5
900 C      TIME BETWEEN STATISTICAL UPDATES
910      IDSTAT=ITWEEK
920 C      STOP AFTER SIMULATION INQTR QUARTERS
930      ISTOP=INQTR*ITQTR
940 C      PLACE INITIAL MANAGEMENT AND DATA COLLECTION EVENTS ON
```

```
950      C      THE FUTURE EVENTS LIST.
960      C      STAT--REVIEW STOCK STATUS
970      CALL ENTER(ISTOCK,5,0,0,0)
980      C      LEVEL--COMPUTE INV CONTROL LEVELS
990      CALL ENTER(ITLEVL,6,0,0,0)
1000     C      SSTAT--ACCUMULATE STATUS STATISTICS
1010     CALL ENTER(ISTAT,11,1,0,0)
1020     C      ITOUT--END OF SIMULATION PERIOD
1030     CALL ENTER(ISTOP,10,0,0,0)
1040     C
1050     C      CREATE FORECAST EVENT
1060     C
1070     100 CONTINUE
1080     ITFOR=ITQTR
1090     IDFOR=ITQTR
1100     C      FORUPD--UPDATE DEMAND HISTORY FILES
1110     CALL ENTER(ITFOR,9,0,0,0)
1120     C      DEMPAR--GENERATE DEMAND
1130     CALL ENTER(100,12,0,0,0)
1140     C
1150     C      CANCLB--CANCELLATION REVIEW EVENT GOES HERE--
1160     C      CANCELLATIONS ARE NOT SIMULATED IN THIS STUDY
1170     C
1180     MBODAY=100
1190     IDCANB=ITMNTN
1200     C
1210     C      INITIALIZE FOR PLOT OF STOCK HISTORY
1220     C
1230     IF(ISTRAC.LE.0) GO TO 200
1240     CALL ENTER(ITRACE,13,0,0,0)
1250     200 CONTINUE
1260     RETURN
1270     END
1280     $      ENDJOB
```

Subroutine: INITEM

Function:

This routine initializes the Item Data File by reading input from File 07, and then performs item-related initializing calculations.

Description:

Input may be provided to this routine in either binary or BCD format. The specific type of input is determined by the variable INTYPE. A detailed description of data contained on file 07 is presented in Vol I, Chap VII.

After reading information on a given item, INITEM then performs several calculations. First, it zeros the demand history accumulators NRETAC, NDEMAC, and NREQAC used to record demand activity for each given item. Inventory status variables and associated pointers are then updated. In the present coding, all due-in inventories are assumed to be on hand; consequently, INITEM increases the variable INVACT(N) by the amount of due-in inventory, and sets the variable INV DUE(N) to zero.

Next, the demand history arrays are initialized using the first NDHIS periods of data recorded in the Demand Driver File. See Vol I, Chap IV, for definition of these data elements.

Finally, subroutine INITEM initializes the variables IBOPOH(J) and IBOPOR(J). These variables record the initial and on order inventories at the beginning of the simulation run.

If an end of file is encountered in reading File 07, subroutines OUT, OUTCST, and PLOTR are called to write out performance statistics summaries.

```
20 $ IDENT WP0287,ADDSC-CALLAHAN
30 $ FORTY DECK
40 $ PRMFL C*,W,S,REQS/INITEM.O
50 $ REMOTE P*,AC
60 $ REMOTE $$,AC
70 SUBROUTINE INITEM
80 C*****INITEM*****
85 CHARACTER ALC,FSN,UM,NOUN,MGTCD
90 COMMON/FSN/ALC,FSN(4),UM,NOUN(2),MGTCD(4),IOH,IOR,IPPL,IR
100 COMMON/GSLF/GSLF
110 COMMON/IDBUG/IDBUG
120 COMMON/ITDAY /ITDAY
130 COMMON/ITMNT/ITMNT
140 COMMON/NITEM/NITEM
150 COMMON/NDEM/NDEM
160 COMMON/NDHIS/NDHIS
170 COMMON/INLU/INLU
180 COMMON/INTYPE/INTYPE
190 COMMON/IEBUG/IEBUG
200 COMMON/IBOP/IBOP(3),IBOPOR(3)
210 COMMON/IDEMND/IDEMND(1,24)
220 COMMON/RMREQS/RMREQS(1)
230 COMMON/INVACT/INVACT(1)
240 COMMON/NORDPT/NORDPT(1)
250 COMMON/NDEMAC/NDEMAC(1)
260 COMMON/NRETAC/NRETAC(1)
270 COMMON/NREQAC/NREQAC(1)
280 COMMON/NDEMND/NDEMND(1,24)
290 COMMON/NRETUR/NRETUR(1,24)
300 COMMON/NREQ/NREQ(1,24)
310 COMMON/NDENT/NDENT(1)
320 COMMON/INVDUE/INVDUE(1)
330 COMMON/NBOPT/NBOPT(1)
340 COMMON/NBOTU/NBOTU(1)
350 COMMON/REQSIZ/REQSIZ(1)
360 COMMON/REQMAD/REQMAD(1)
370 COMMON/LTPROD/LTPROD(1)
380 COMMON/LTADM/LTADM(1)
390 COMMON/UCOST/UCOST(1)
400 COMMON/ADR/ADR(1)
410 COMMON/ISUL/ISUL(1)
420 COMMON/IREQ /IREQ(1,24)
430 COMMON/IRETUR/IRETUR(1,24)
440 COMMON/IRL/IRL(1)
450 COMMON/ITL/ITL(1)
460 COMMON/IROL/IROL(1)
470 COMMON/IRQTY/IRQTY(1)
480 COMMON/RMTBR /RMTBR(1)
490 COMMON/RMEAN/RMEAN(1)
500 COMMON/RTREND/RTREND(1)
510 COMMON/RMAD /RMAD(1)
520 COMMON/RERSUM/RERSUM(1)
530 COMMON/XNT /XNT(1)
```

p. 2 of 4

```

540      COMMON/GEQ/GEQ(3)
550      COMMON/GEQF/GEQF(3)
560      COMMON/ICDFOR/ICDFOR
570      C
580      C
590      C          SET NUMBER OF PERIODS OF DATA INPUT
600      C
610      IDPER=NDEM
620      C
630      C          READ DEMAND DATA FOR ITEM N FROM LOGICAL UNIT LR
640      LR=INLU
650      IKNT=0
660      DO 100 N=1,NITEM
670      10 CONTINUE
680      C
690      C          READ ITEM DATA INPUT FROM FILE LR
700      C
710      IF(INTYPE.EQ.2) GO TO 20
720      C
730      C          READ BCD INPUT
740      C
750      IKNT=IKNT+1
760      READ(LR,8000,END=200) ALC,FSN,UM,UCOST(N),NOUN,MGTCD,IOH,
770      & LTADM(N),LTPROD(N),IPPL,IPPPR
780      C
790      RIPPPR=FLOAT(IPPPR)/100.
800      IF(IEBUG.EQ.1)WRITE(6,8010)IKNT,ALC,FSN,UM,UCOST(N),NOUN,
810      & IOH,IOR,LTADM(N),LTPROD(N),IPPL,RIPPPR
820      IF(IEBUG.EQ.1)WRITE(6,8015)(I,I=1,10)
830      C
840      C          READ DEMAND, RETURNS, AND REQ-FREQUENCY
850      C
860      READ(LR,8000)(IDEMND(N,J),J=1,IDPER)
870      IF(IEBUG.EQ.1)WRITE(6,8020)(IDEMND(N,J),J=1,IDPER)
880      READ(LR,8000)(IRETUR(N,J),J=1,IDPER)
890      IF(IEBUG.EQ.1)WRITE(6,8030)(IRETUR(N,J),J=1,IDPER)
900      READ(LR,8000)(IREQ(N,J),J=1,IDPER)
910      IF(IEBUG.EQ.1)WRITE(6,8040)(IREQ(N,J),J=1,IDPER)
920      GO TO 50
930      C
940      C          READ BINARY DATA
950      C
960      20 CONTINUE
970      IKNT=IKNT+1
980      READ(LR)ALC,FSN,IR,UM,UCOST(N),NOUN,MGTCD,IOH,IOR,
990      & LTADM(N),LTPROD(N),IPPL,RIPPPR
1020      IF(IEBUG.EQ.1)WRITE(6,8010)IKNT,ALC,FSN,UM,UCOST(N),NOUN,
1030      & MGTCD,IOH,IOR,LTADM(N),LTPROD(N),IPPL,RIPPPR
1040      READ(LR)ALC,FSN,IR,IDEMND
1050      IF(IEBUG.EQ.1)WRITE(6,8020)(IDEMND(N,J),J=1,IDPER)
1060      READ(LR)ALC,FSN,IR,IRETUR
1070      IF(IEBUG.EQ.1)WRITE(6,8030)(IRETUR(N,J),J=1,IDPER)
1080      READ(LR)ALC,FSN,IR,IREQ
1090      IF(IEBUG.EQ.1)WRITE(6,8040)(IREQ(N,J),J=1,IDPER)
1100      C          WRITE INPUT DATA TO FILE 09

```



P 3 44

```

1110 C
1120 C
1130 C
1140 8000 FORMAT(V)
1150 8010 FORMAT(/I5,1X,A2,1X,A2,A4,A6,A3,1X,A2,F11.2,1X,A6,A4,
1160 & T53,2A1,A4,A2,2X,2I7,3I6,F5.2)
1170 8015 FORMAT(T21,10I10)
1180 8020 FORMAT('IDEMND DEMAND/QTR',(T21,10I10))
1190 8030 FORMAT('IRETUR RETURN/QTR',(T21,10I10))
1200 8040 FORMAT('IREQ REQ /QTR',(T21,10I10))
1210 C
1220 50 CONTINUE
1230 C INDICATE ITEM HAS NDHIS PERIODS OF DEMAND HISTORY
1240 C
1250 NDENT(N)=NDHIS
1260 C
1270 C ZERO DEMAND HISTORY RECORDS
1280 NRETAC(N)=0
1290 NDEMAC(N)=0
1300 NREQAC(N)=0
1310 DO 65 J=1,NDHIS
1320 65 NDEMND(N,J)=IDEMND(N,J)
1330 C SET INVENTORY DUE-IN TO ZERO
1340 70 INVDUE(N)=0
1350 NBOTU(N)=0
1360 NBOPT(N)=0
1370 NORDPT(N)=0
1380 C
1390 C LOAD DEMAND HISTORY ARRAYS
1400 C
1410 KK=NDHIS
1420 DO 1 I=1,NDHIS
1430 NDEMND(N,KK)=IDEMND(N,I)
1440 NRETUR(N,KK)=IRETUR(N,I)
1450 NREQ(N,KK)=IREQ(N,I)
1460 KK=KK-1
1470 1 CONTINUE
1480 C
1490 C SLIDE DOWN DATA IN DEMAND ARRAYS
1500 C
1510 KK=NDHIS+1
1520 DO 2 I=1,IDPER
1530 IDEMND(N,I)=IDEMND(N,KK)
1540 IRETUR(N,I)=IRETUR(N,KK)
1550 IREQ(N,I)=IREQ(N,KK)
1560 KK=KK+1
1570 2 CONTINUE

```

INITEM (CONT)

p 4 of 4

```
1580 C
1590 C
1600 C          ESTABLISH BEGINNING INVENTORY LEVELS
1610 C
1620          INVACT(N)=IOH+IOR
1630 100 CONTINUE
1640 C
1650 C          INITIALIZE GROSS ON-HAND AND ON-ORDER STATISTICS
1660 C
1670 110 CONTINUE
1680          DO 130 N=1,NITEM
1690          IF(NDENT(N).LT.0) GO TO 130
1700          IF(INVACT(N).LE.0) GO TO 120
1710          IBOPOH(1)=IBOPOH(1)+1
1720          IBOPOH(2)=IBOPOH(2)+INVACT(N)
1730          IBOPOH(3)=IBOPOH(3)+IFIX(UCOST(N)*FLOAT(INVACT(N)))
1740 120 CONTINUE
1750          IF(INVDUE(N).LE.0) GO TO 130
1760          IBOPOR(1)=IBOPOR(1)+1
1770          IBOPOR(2)=IBOPOR(2)+INVDUE(N)
1780          IBOPOR(3)=IBOPOR(3)+IFIX(UCOST(N)*FLOAT(INVDUE(N)))
1790 130 CONTINUE
1800 140 CONTINUE
1810          RETURN
1820 200 WRITE(6,8200)
1830 8200 FORMAT(1H1,///20X,'END OF FILE READING.....')
1840          CALL OUT
1850          CALL OUTCST
1860          CALL PLOTR
1870          STOP
1880          END
1890 $          ENDJOB
```



Subroutine: ITRSLT

Function:

This routine writes details of the performance statistics associated with a given item to File 08.

Description:

This routine first converts recorded values of performance statistics to floating point variables stored in the array RID. It then writes a single binary record for this item to File 08. Record lay outs for this record are defined in Vol I, App B. See Vol I, Chap VIII, for an additional discussion of this routine.

1 04-10-77 12.174

ITRSLT.O OUTPUT ITEM PERFORMANCE STATISTICS TO FILE

C  
C

ITRSLT.O OUTPUT ITEM PERFORMANCE STATISTICS TO FILE 08

SUBROUTINE ITRSLT  
COMMON/FSN/ALC,FSN(4),UM,NOUN(2),MGIED(4),IOH,IOR,IPPL,IPPPR  
COMMON/IDENT/IDENT,MRUN,IREPL  
COMMON/INQTR/INQTR  
COMMON/COSORD/COSORD(3)  
COMMON/ISMORD/ISMORD(30,3)  
COMMON/ILGORD/ILGORD(30,3)  
COMMON/POLICY/ICDEEQ,ICDSL  
COMMON/LTADM/LTADM(1)  
COMMON/LTPROD/LTPROD(1)  
COMMON/UCOST/UCOST(1)  
COMMON/IREQT/IREQT(30,3)  
COMMON/IRETRN/IRETRN(30,3)  
COMMON/IBAKDT/IBAKDT(30,3)  
COMMON/IORDER/IORDER(30,3)  
COMMON/INVDAY/INVDAY(30,3)  
COMMON/IFILLT/IFILLT(30,3)  
DIMENSION RJD(16,10)  
DIMENSION RID(16,10)

ITRSLT  
P. 1 of 2

C  
C  
C

ON FIRST REPLICATION, ZERO THE RJD-ARRAY

IF(IREPL.GT.1) GO TO 20  
DO 10 I=1,INQTR  
DO 10 J=1,10  
RJD(I,J)=0.  
CONTINUE  
CONTINUE

10  
20

C  
C  
C  
C

CONVERT INTEGERS TO FLOATING POINT FOR OUTPUT

TDENT=IDENT  
TCDSL=ICDSL  
TRUN=MRUN  
TLT=LTADM(1)+LTPROD(1)  
ROH=IOH+IOR

C  
C  
C  
C

COMPUTE DIFFERENCES OF I- AND JD- ARRAYS.  
THESE ARE THE OPERATING RESULTS FOR THE CURRENT  
ITEM.

DO 100 I=1,INQTR  
RID(I,1)=IREQT(I,1)-RJD(I,1)  
RID(I,2)=IREQT(I,2)-RJD(I,2)  
RID(I,3)=IRETRN(I,2)-RJD(I,3)  
RID(I,4)=IBAKDT(I,1)-RJD(I,4)  
RID(I,5)=IBAKDT(I,2)-RJD(I,5)  
RID(I,6)=IORDER(I,2)-RJD(I,6)  
RID(I,7)=INVDAY(I,2)-RJD(I,7)

01 04-16-77 12.178

ITRSLT.O OUTPUT ITEM PERFORMANCE STATISTICS TO FILE

RID(I,8)=IFILLT(I,1)\*RJD(I,8)  
RID(I,9)=IFILLT(I,2)\*RJD(I,9)  
RID(I,10)=COSORD(1)\*FLOAT(ISMORD(I,1))+  
COSORD(2)\*FLOAT(ILGORD(I,1)) = RJD(I,10)

8  
100 CONTINUE

WRITE RESULTS TO FILE 08

WRITE(8)TDENT,TCDSL,TRUN,ALC,FSN,MGTGD,UCOST(1),TLT,  
ROH,RID

RECORD CURRENT VALUES FOR USE ON NEXT ITEM

DO 300 I=1,INQTR  
DO 300 J=1,13  
RJD(I,J)=RID(I,J)+RJD(I,J)  
300 CONTINUE  
RETURN  
END

ITRSLT,

P. 2 of 2

Subroutine: LEVEL

Function:

This routine computes new inventory control levels for each item being simulated.

Description:

Subroutine LEVEL first calls subroutine FOR576(N) to update estimates of annual demand rate, the standard deviation of demand in the leadtime, and average requisition size. Next, subroutine LEVELN(N) is called to compute new control levels for item N. After new control levels have been computed for each item, LEVEL creates the next level calculation event (event type 6), and puts it in the Future Events List.

01 04-16-77 12.076

LEVEL

p.1 of 1

```
SUBROUTINE LEVEL
COMMON/COSHRT/COSHRT
COMMON/IDLEVL/IDLEVL
COMMON/ITLEVL/ITLEVL
COMMON/NITEM/NITEM
COMMON/NDENT/NDENT(1)
DO 10 N=1,NITEM
```

C  
C  
C  
C

```
UPDATE ESTIMATES OF ANNUAL DEMAND RATE(ADR),RSIGLT,
AND AVERAGE REQUISITION SIZE
```

```
CALL FOR576(N)
```

```
1457 DO LOOP INDEX N MAY NOT BE REDEFINED IN CALL OR ABNORMAL FUNCTION
```

C  
C  
C

```
COMPUTE NEW INVENTORY CONTROL LEVELS
```

```
CALL LEVELN(N)
```

```
1457 DO LOOP INDEX N MAY NOT BE REDEFINED IN CALL OR ABNORMAL FUNCTION
100 CONTINUE
```

C  
C  
C

```
CREATE NEXT LEVELING EVENT
```

```
ITLEVL=ITLEVL + IDLEVL
CALL ENTER(ITLEVL,6,0,0,0)
RETURN
END
```

Subroutine: LEVELN

Function:

This routine computes new reorder, termination, retention, and support levels for a given item N.

Description:

This routine is controlled by the management codes ICDEOQ, ICDSL, and ICDSLL provided as input through File 05. These codes specify formulas to be used in computing order quantities, establishing safety levels, and limiting safety levels, respectively. The meanings of these codes are defined in detail in Vol I, Chap VII.

After order quantity and safety level values are computed, they are bounded by input parameters EOQMIN, EOQMAX, SLMIN, and SLMAX. The safety level bounds are dependent upon bounding flag code ICDSLL.

With the current coding, safety level is set to be no less than SLMIN months of supply. Also, the safety level is limited to be no more than either (a) three times the standard deviation of demand in the leadtime, or (b) the expected number of units to be demanded in the leadtime, whichever is smaller.

The routine concludes by computing termination, retention, and support levels using the parameters GTLF, GRLF, and GSULF.

## SUBROUTINE LEVELN(N)

THIS ROUTINE COMPUTES REORDER, STOCK OBJECTIVE, RETENTION,  
TERMINATION, AND SUPPORT LEVELS.

```

COMMON/IHBUG/IHBUG
COMMON/COSHRT/COSHRT
COMMON/COSHLd/COSHLd
COMMON/COSORD/COSORD(3)
COMMON/CSTBRK/CSTBRK
COMMON/GSULF/GSULF
COMMON/GRLF/GRLF
COMMON/GSLF/GSLF
COMMON/GTLF/GTLF
COMMON/ITLEVl/ITLEVl
COMMON/IDLEVl/IDLEVl
COMMON/NITEM/NITEM
COMMON/POLICE/ICDEQ, ICDSL, EOQMAX, EOQMIN, SLMAX, SLMIN, RLF, TLF, SULF
COMMON/ADR/ADR(50)
COMMON/LTADM/LTADM(50)
COMMON/LTPROD/LTPROD(50)
COMMON/IRQTY/IRQTY(50)
COMMON/IRL/IRL(50)
COMMON/IROL/IROL(50)
COMMON/ISUL/ISUL(50)
COMMON/ITL/ITL(50)
COMMON/RSIGLT/RSIGLT(50)
COMMON/REQSIZ/REQSIZ(50)
COMMON/UCOST/UCOST(50)
DATA Z/1.0/
DATA ITLMIN,IRLMIN/99999999,99999999/

```

## COMPUTE PLANNING FACTORS

```

AMDA=COSHRT
RLTM=LTADM(N)+LTPROD(N)
IF(RLTM,LT.1.)RLTM=0.5

```

\*\*\*\*

```

AD=ADR(N)
RLT=AD*RLTM/12.
RMR=AD/12.
UC=UCOST(N)
ADDR=UC*AD

```

## ESTIMATE STD DEVIATION OF FORECAST ERRORS

```

SIG=RSIGLT(N)

```

```

SET COR EQUAL TO SMALL PURCHASE ORDER COST
COR=COSORD(1)

```

## BRANCH BY EOQ FORMULA CODE



01 04-16-77 12.082

LEVELN,  
P. 2 of 4

```
C      GO TO (110,120,130,140,150,160,170,180,190),ICDEOQ
C
C      2 FEB 70 GUIDELINE LTR POLICY
C
110  IF(ADDR,GE.1000.) GO TO 62
      Q=12.*RMR
      GO TO 200
62  IF(ADDR,GE.5000.) GO TO 64
      Q=6.*RMR
      GO TO 200
64  Q=3.*RMR
      GO TO 200
C
C      AFLC 57-6 POLICY--DEC 1976
C
120  Q=SQRT(2.*COR*AD/(COSHLD*UC))
      ACOSQ=Q*UC
      IF(ACOST.LT.CSTBRK) GO TO 200
      COR=COSORD(2)
      Q=SQRT(2.*COR*AD/(COSHLD*UC))
      GO TO 200
130  CONTINUE
140  CONTINUE
150  CONTINUE
160  CONTINUE
170  CONTINUE
180  CONTINUE
190  CONTINUE
      WRITE(6,8195)ICDEOQ,ICDSL
8195  FORMAT('***LEVELN--UNDEFINED FORMULA CODE,...',
&      ' ICDEOQ=',I3,' ICDSL=',I3)
      STOP
C
C      CHECK ORDER SIZE LIMITS
C
200  CONTINUE
      EMX=EOQMAX*RMR
      IF(Q.GT.EMX) Q=EMX
      EMX=EOQMIN*RMR
      IF(Q.LT.EMX) Q=EMX
      IF(Q.LT. 1.)Q= 1.
C
C      BRANCH BY SAFETY LEVEL FORMULA CODE ICDSL
C
      GO TO (310,320,330,340,350,360,370,380,390),ICDSL
C
C      2 FEB 70 GUIDELINE LTR POLICY
C
310  SL=1.*RMR
      GO TO 500
C
C      23 AUG 68 GUIDELINE LTR POLICY
```

1 04-16-77 12.082

LEVELN,  
p. 3 of 4

```
C
320 SL=0.25*RLT
    GO TO 500

C
C      AFLCM 57-6 POLICY
C
330 Z=SQRT(REQSIZ(N))
    GO TO 358

C
C      PT=FORMULA TO MINIMIZE UNITS BACKORDERED
C
340 Z=1,
    GO TO 358

C
C      PT=FORMULA TO MINIMIZE REQUISITIONS BACKORDERED
C
350 Z=REQSIZ(N)

C
358 CONTINUE
    RNUM=AMDA*SIG*(1.-EXP(-1.414*Q/SIG))
    DNOM=2.*COSHL D*UC*Z*1.414*Q
    RK=0.707*A LOG(RNUM/DNOM)
    SL=RK*SIG
    GO TO 500

C
360 CONTINUE
370 CONTINUE
380 CONTINUE
390 CONTINUE
    WRITE(6,8195)ICDEOQ,ICDSL
    STOP
*****
*****
500 CONTINUE

C
C      LIMIT SAFETY LEVEL
C      FIRST,CHECK MINIMUM
    SLM=SLMIN*RM R
    IF(SL.LT.SLM)SL=SLM

C
C      LIMITS SL TO LESS THAN LEADTIME DEMAND
C
    SLM=RLT*RM R
    IF(SL.GT.SLM)SL=SLM

C
C      LIMIT SL TO LESS THAN 3*SIG
C
    SLM=3.*SIG
    IF(SL.GT.SLM)SL=SLM
**
```

```

*****
C
C      COMPUTE LEVELS
C
      IROTY(N)=Q+0.5
      IROL(N)=SL+RLT+0.5
      ITL(N)=SLMAX*RMR+RLT+GTLF*RMR+0.5
      IRL(N)=FLOAT(ITL(N))+GRLF*RMR+0.5
      IF(ITL(N).LE.ITLMIN) ITL(N)=ITLMIN
      IF(IRL(N).LE.IRLMIN) IRL(N)=IRLMIN
      ISUL(N)=GSULF*RLT
3000  CONTINUE
      ROL=FLOAT(IROL(N))
      IF(INBUG.NE.1) RETURN
      WRITE(6,8903)N,IROTY(N),IROL(N),ITL(N),IRL(N),ISUL(N)
8903  FORMAT(4X,'***LEVELN-#N=',I5,' IROTY=',I5,' IROL=',I5,
&        ' ITL=',I5,' IRL=',I5,' ISUL=',I5)
      RETURN
END

```

Subroutine: MAIN

Function:

MAIN is the primary INSSIM routine. This routine coordinates input of data, initialization of the simulation, event sequencing, and output reporting.

Description:

This routine is described in detail in Vol I, Chap V.

MAIN

p. 1 of 9

```
20      $      IDENT      WP0287,ADDSC-CALLAHAN
30      $      FORTY      DECK
40      $      OPTION     FORTRAN
50      $      PRMFL      C*,W,S,REQS/MAIN.0
60      $      LIMITS     5,32K
70      $      REMOTE     P*,AC
80      $      REMOTE     $$,AC
90      $      CHARACTER TEXT*40
100     $      INTEGER PX(52),PY(52,4)
110     *-----
120     COMMON/BPER/BPER
130     COMMON/COSHLB/COSHLB
140     COMMON/COSORD/COSORD(3)
150     COMMON/CSTBRK/CSTBRK
160     COMMON/COSHRT/COSHRT
170     COMMON/FSN/ALC,FSN(4),UM,NOUN(2),MGTCB(4),IOH,IOR,IPPL,IR
180     COMMON/GMRQF/GMRQF
190     COMMON/GRLF/GRLF
200     COMMON/GROQF/GROQF
210     COMMON/GSLF/GSLF
220     COMMON/GSULF/GSULF
230     COMMON/GTLF/GTLF
240     COMMON/GUIDI/ICDGID,NPH,NPOLCY,IDJXR,IDJXS,SHORT(16)
250     COMMON/GUIDII/DEMFA,ALTMX,PLTMX,GRPSEL,IBEGIN,IEND
260     COMMON/ICDFOR/ICDFOR
270     COMMON/ICDSIG/ICDSIG
280     COMMON/IDBUG/IDBUG
290     COMMON/IEBUG/IEBUG
300     COMMON/IGBUG/IGBUG
310     COMMON/IFBUG/IFBUG
320     COMMON/IHBUG/IHBUG
330     COMMON/IDDIV/IDDIV
340     COMMON/IDENT/IDENT,IRUN,IREFL
350     COMMON/IDLEVL/IDLEVL
360     COMMON/IDSTAT/IDSTAT
370     COMMON/IDTHQ/IDTHQ
380     COMMON/IKDEM/IKDEM
390     COMMON/INLU/INLU
400     COMMON/INTYPE/INTYPE
410     COMMON/INQTR/INQTR
420     COMMON/IOBLIG/IOBLIG
430     COMMON/IPFOR/IPFOR
440     COMMON/IQTRND/IQTRND
450     COMMON/ISTAT/ISTAT
460     COMMON/ISTOCK/ISTOCK,IDSTOC
470     COMMON/ISTOP/ISTOP
480     COMMON/ITCAND/ITCAND,IDCAND
```

```
490 COMMON/ITDAY/ITDAY
500 COMMON/ITDIV/ITDIV
510 COMMON/ITFOR/ITFOR,IDFOR
520 COMMON/ITHQ/ITHQ
530 COMMON/ITINV/ITINV
540 COMMON/ITIME/ITIME
550 COMMON/ITLEV/ITLEV
560 COMMON/ITMTH/ITMTH
570 COMMON/ITQTR/ITQTR
580 COMMON/ITWEEK/ITWEEK
590 COMMON/ITYEAR/ITYEAR
600 COMMON/MAXB/MAXB
610 COMMON/MBODAY/MBODAY
620 COMMON/NBPER/NBPER
630 COMMON/NBMAX/NBMAX
640 COMMON/NDEM/NDEM
650 COMMON/NDHIS/NDHIS
660 COMMON/NENTRY/NENTRY
670 COMMON/NFEMAX/NFEMAX
680 COMMON/NFIRST/NFIRST
690 COMMON/NITEM/NITEM
700 COMMON/NLOC/NLOC
710 COMMON/NLOCBK/NLOCBK
720 COMMON/NRELP/NREPL
730 COMMON/NTIME/NTIME
740 COMMON/POLICY/ICDEQ,ICDSL,EQMAX,EQMIN,SLMAX,SLMIN,RLF,
750 COMMON/ADR/ADR(1)
760 COMMON/IDEMND/IDEMND(1,24)
770 COMMON/IRETUR/IRETUR(1,24)
780 COMMON/IREQ/IREQ(1,24)
790 COMMON/INVACT/INVACT(1)
800 COMMON/INVDUE/INVDUE(1)
810 COMMON/IRL/IRL(1)
820 COMMON/IROL/IROL(1)
830 COMMON/IRQTY/IRQTY(1)
840 COMMON/ISUL/ISUL(1)
850 COMMON/ITL/ITL(1)
860 COMMON/LTADM/LTADM(1)
870 COMMON/LTPROD/LTPROD(1)
880 COMMON/XNT /XNT(1)
890 COMMON/NBOPT/NBOPT(1)
900 COMMON/NBOTU/NBOTU(1)
910 COMMON/NDEMAC/NDEMAC(1)
920 COMMON/NRETAC/NRETAC(1)
930 COMMON/NREQAC/NREQAC(1)
940 COMMON/NDEMND/NDEMND(1,24)
950 COMMON/NRETUR/NRETUR(1,24)
960 COMMON/NREQ/NREQ(1,24)
970 COMMON/NBENT/NBENT(1)
980 COMMON/NORDPT/NORDPT(1)
990 COMMON/REQMAD/REQMAD(1)
1000 COMMON/REQSIZ/REQSIZ(1)
1010 COMMON/RERSUM/RERSUM(1)
```



```
1020 COMMON/RMAD /RMAD(1)
1030 COMMON/RMEAN/RMEAN(1)
1040 COMMON/RMREQS/RMREQS(1)
1050 COMMON/RMTBR /RMTBR(1)
1060 COMMON/RSIGLT/RSIGLT(1)
1070 COMMON/RTREND/RTREND(1)
1080 COMMON/UCOST/UCOST(1)
1090 COMMON/ILOCFE/ILOCFE(500)
1100 COMMON/JFSN/JFSN(500)
1110 COMMON/JPOINT/JPOINT(500)
1120 COMMON/JPRIOR/JPRIOR(500)
1130 COMMON/JQTY/JQTY(500)
1140 COMMON/JTIME/JTIME(500)
1150 COMMON/JTYPE/JTYPE(500)
1160 COMMON/IBACPT/IBACPT(100)
1170 COMMON/IDFSNB/IDFSNB(100)
1180 COMMON/ILOCBK/ILOCBK(100)
1190 COMMON/IPRIOR/IPRIOR(100)
1200 COMMON/IQTYB/IQTYB(100)
1210 COMMON/ITMBAC/ITMBAC(100)
1220 COMMON/IBOP/IBOP(3),IBOPOR(3)
1230 COMMON/IBAUTH/IBAUTH(12)
1240 COMMON/IBPROJ/IBPROJ(12)
1250 COMMON/GEQO/GEQO(3)
1260 COMMON/GEQOF/GEQOF(3)
1270 COMMON/IBACKI/IBACKI(30,3)
1280 COMMON/IBACKT/IBACKT(30,3)
1290 COMMON/IBAKDI/IBAKDI(30,3)
1300 COMMON/IBAXDT/IBAXDT(30,3)
1310 COMMON/ICANCL/ICANCL(30,3)
1320 COMMON/IDISPS/IDISPS(30,3)
1330 COMMON/IEXPED/IEXPED(30,3)
1340 COMMON/IFILLI/IFILLI(30,3)
1350 COMMON/IFILLT/IFILLT(30,3)
1360 COMMON/INVOH/INVOH(30,3)
1370 COMMON/INVDAY/INVDAY(30,3)
1380 COMMON/INVOR/INVOR(30,3)
1390 COMMON/IORDER/IORDER(30,3)
1400 COMMON/IRATON/IRATON(30,3)
1410 COMMON/IRECET/IRECET(30,3)
1420 COMMON/IREQC /IREQC(30,3)
1430 COMMON/IREQI /IREQI(30,3)
1440 COMMON/IREQT/IREQT(30,3)
1450 COMMON/IRETRN/IRETRN(30,3)
1460 COMMON/ISHIPI/ISHIPI(30,3)
1470 COMMON/ISHIPT/ISHIPT(30,3)
1480 COMMON/ITERM /ITERM(30,3)
1490 COMMON/ITRACE/ITRACE,ISTRAC
1500 DIMENSION CSHORT(4)
```

```

1510 *-----
1520 C
1530 *      SET CODES FOR GUIDELINE REVISIONS
1540      NPH=20
1550      GTLF=24.
1560      GRLF=12.
1570      GSULF=0.
1580      GSLF=1.
1590      GROQF=1.
1600 C
1610 C
1620 C      READ INPUT DATA
1630 C
1640 10  CONTINUE
1650      WRITE(6,8000)
1660 8000  FORMAT(1H1, T30, 'INVENTORY SYSTEM SIMULATOR'//T34,
1670 &      'RUN PARAMETERS'///)
1680 C
1690 C      READ RUN IDENTIFICATION(CARD TYPE C1)
1700 C
1710      READ(5,8001,END=9999)IDENT,TEXT
1720 8001  FORMAT(V)
1730      WRITE(6,8002)IDENT,TEXT
1740 8002  FORMAT(' (C1) RUN-ID. ',I6, ' TITLE. ',A40)
1750 C
1760 C      READ OUTPUT CONTROLS(CARD CODE C2)
1770 C
1780      READ(5,8003)ITWRT,IOUT,IGRAPH,IPUNCH
1790 8003  FORMAT(V)
1800      WRITE(6,8004)ITWRT,IOUT,IGRAPH,IPUNCH
1810 8004  FORMAT(/// (C2) OUTPUT CONTROLS...(NOTE. 1=YES) //
1820 &      ITWRT,T16,IT.WRITE=,I3//
1830 &      IOUT,T16,SUMMARY =,I3//
1840 &      IGRAPH,T16,GRAPHS =,I3//
1850 &      IPUNCH,T16,PUNCH =,I3)
1860 C
1870 C      READ DEBUG FLAGS
1880 C
1890      READ(5,8005)IDBUG,IEBUG,IFBUG,IGBUG,IHBUG,ITRACE,ISTRAC
1900      WRITE(6,8005)IDBUG,IEBUG,IFBUG,IGBUG,IHBUG,ITRACE,ISTRAC
1910 8005  FORMAT(/// (C3) DEBUG FLAGS //
1920 &      T16,IDBUG =,I3//
1930 &      T16,IEBUG =,I3//
1940 &      T16,IFBUG =,I3//
1950 &      T16,IGBUG =,I3//
1960 &      T16,IHBUG =,I3//
1970 &      ITRACE,T16,START TRACE AT',I6, ' FOR ITEM 1' /
1980 &      ISTRAC,T16,STOP TRACE AT',I6)
1990 C
2000 C      DEFINE ITEM INPUT FILES
2010 C
2020      READ(5,8006)INLU,INTYPE,NDEM
2030      WRITE(6,8010)INLU,INTYPE,NDEM
2040 8010  FORMAT(/// (C4) ITEM INPUT FILES //
2050 &      INLU,T16,FILE =,I3/
2060 &      INTYPE,T16,TYPE =,I3, (1 = BCD; 2 = BINARY)
2070 &      NDEM,T16,QTRS =,I3)
2080 C

```

p. 4 of 9

p. 5 of 9

```

2090 C READ MANAGEMENT METHOD CODES(CARD TYPE C5)
2100 C
2110 READ(5,8003)ICDFOR,ICDSIG,ICDEOQ,ICDSL,ICDSSL,ICDBG,ICDSR
2120 WRITE(6,8050)ICDFOR,ICDSIG,ICDEOQ,ICDSL,ICDSSL,ICDBG,ICDSR
2130 8050 FORMAT(IH1, / (C5) MANAGEMENT METHODS TO BE USED //
2140 & ICDFOR ,T16, FORECAST FORMULA = ,I3//
2150 & ICDSIG ,T16, STD DEV FORMULA = ,I3//
2160 & ICDEOQ ,T16, EOQ FORMULA = ,I3//
2170 & ICDSL ,T16, SAFETY STK CODE = ,I3//
2180 & ICDSSL ,T16, SAFETY LIMIT CODE = ,I3//
2190 & ICDBG ,T16, BUDGET GUIDE CODE = ,I3//
2200 & ICDSR ,T16, RETURNS CODE = ,I3)
2210 C
2220 C READ MANAGEMENT PARAMETERS(CARD CODE C6)
2230 C
2240 READ(5,8003)EQQMIN,EOQMAX,SLMIN,SLMAX
2250 WRITE(6,8060)EQQMIN,EOQMAX,SLMIN,SLMAX
2260 8060 FORMAT(/// (C6) MANAGEMENT PARAMETERS ///
2270 & EQQMIN ,T16, MIN EQQ(MNTHS) ,T40,F10.4//
2280 & EOQMAX ,T16, MAX EQQ(MNTHS) ,T40,F10.4//
2290 & SLMIN ,T16, MIN SAFETY LV(MNTHS) ,T40,F10.4//
2300 & SLMAX ,T16, MAX SAFETY LV(MNTHS) ,T40,F10.4)
2310 C
2320 C READ SYSTEM PARAMETERS(CARD TYPE C7)
2330 C
2340 READ(5,8003)COSHLD,CSHORT,COSORD(1),COSORD(2),CSTBRK
2350 WRITE(6,8070)COSHLD,CSHORT,COSORD(1),COSORD(2),CSTBRK
2360 8070 FORMAT(/// (C7) SYSTEM PARAMETERS ///
2370 & COSHLD ,T16, HOLDING COST/$-INV ,T40,F10.4//
2380 & CSHORT ,T16, SHORTAGE COST ,T40,F10.4//
2390 & COSORD(1) ,T16, SMALL ORDER COST ,T40,F10.4//
2400 & COSORD(2) ,T16, LARGE ORDER COST ,T40,F10.4//
2410 & CSTBRK ,T16, COST BREAK-POINT ,T40,F10.4)
2420 C
2430 C READ SIMULATION SIZE PARAMETERS(CARD TYPE C8)
2440 C
2450 READ(5,8003)NRUN,INQTR,NREPL,NITEM,NDHIS
2460 WRITE(6,8080)NRUN,INQTR,NREPL,NITEM,NDHIS
2470 8080 FORMAT(/// (C8) SIMULATION SIZE ///
2480 & NRUN ,T16, NUMBER OF RUNS ,T40,I5//
2490 & INQTR ,T16, NUMBER OF QUARTERS ,T40,I5//
2500 & NREPL ,T16, NO. OF REPLICATIONS ,T40,I5//
2510 & NITEM ,T16, NO. OF ITEMS/REPL ,T40,I5//
2520 & NDHIS ,T16, NO. OF HISTORY QTRS ,T40,I5)
2530 C
2540 C END OF RUN DEFINITION INPUT
2550 C
2560 C

```

```

2570 C*****
2580 C
2590 C          BEGIN SIMULATION
2600 C
2610 C*****
2620      DO 99 MRUN=1,NRUN
2630      IRUN=MRUN
2640      COSHRT=CSHORT(MRUN)
2650      WRITE(6,8090)COSHRT
2660 8090  FORMAT(IH1,25('****'),2(/'**'),
2670 &      I20,'BEGIN SIMULATION WITH COSHRT =',F10.4,
2680 &      2(/'**'),25('****'))
2690 C
2700 C          INITIALIZE RANDOM NUMBER STREAM
2710 C
2720      R=RANDU(-.1)
2730 C
2740 C
2750      REWIND INLU
2760 C
2770 C          BEGIN REPLICATION LOOP
2780 C
2790      CALL ZERO
2800      DO 95 KREPL=1,NREPL
2810      IPLOT=0
2820      IREPL=KREPL
2830 15 CONTINUE
2840 C
2850 C          INITIALIZE THE FUTURE EVENTS LIST(INITAL),
2860 C          AND READ ITEM DEMAND DATA (INITEM).
2870 C
2880      CALL INITAL
2890      CALL INITEM
2900      IF(IDBUG.NE.1) GO TO 16
2910      CALL WRIFEL
2920 16 CONTINUE
2930 C
2940 C*****
2950 C
2960 C
2970 C          REMOVE NEXT EVENT FROM FUTURE EVENTS LIST
2980 C          ***BRANCH BY TYPE OF TRANSACTION***
2990 20 CALL REMOVE(itime,ktype,ip3,ip4,ip5)
3000      GO TO ( 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 33,
3010      C, 36, 37, 38, 39),ktype
3020 C
3030 C*****
3040 C
3050 21 CONTINUE
3060 C          REFLECT RECEIPT OF TRANSACTION
3070 C          REQUISITION
3080 C
3090      CALL REQ(ip3,ip4,ip5,itime)
3100      GO TO 20
3110 22 CONTINUE
3120 C          RECEIPT OF SHIPMENT

```

p. 6 of 9



```

3130 C      REFLECT RECEIPT
3140      CALL RECEIV(IP3,IP4)
3150      GO TO 20
3160      23 CONTINUE
3170 C
3180 C      REVIEW BACKORDERS.  CANCEL THOSE OLDER THAN MBODAY DAYS
3190 C
3200      CALL CANCLB
3210      GO TO 20
3220 C
3230 C      SERVICEABLE RETURN EVENT
3240 C
3250      24 CALL RET(IP3,IP4,ITIME)
3260      GO TO 20
3270      25 CONTINUE
3280 C      STATUS REVIEW
3290      CALL STATUS
3300      GO TO 20
3310      26 CONTINUE
3320 C      LEVELS COMPUTATION
3330      CALL LEVEL
3340      GO TO 20
3350      27 CONTINUE
3360 C      BUY GUIDELINE
3370      CALL GUIDE
3380      GO TO 20
3390      28 CONTINUE
3400 C      BUDGET REVIEW
3410      CALL BUDGET
3420      GO TO 20
3430      29 CONTINUE
3440 C      FORECAST UPDATE
3450      CALL FORUPD
3460      GO TO 20
3470      30 CONTINUE
3480 C*****
3490 C
3500 C      END OF RUN
3510 C
3520 C*****
3530      IF(ITWRT.EQ.1) CALL ITRSLT
3540      IF(KREPL.LT.NREPL) GO TO 95
3550      300 CONTINUE
3560      IF(IDBUG.EQ.1) CALL WRIFEL
3570      IF(IOUT.NE.1) GO TO 90
3580      CALL OUT
3590      CALL OUTCST
3600      90 CONTINUE
3610      WRITE(6,302)
3620      IF(IGRAPH.EQ.1) CALL PLOTR
3630      IF(IPUNCH.NE.1) GO TO 233
3640      DO 232 J=1,3
3650      DO 232 I=1,INQTR

```

P. 8 of 9

```

3660      WRITE(6,301)IDENT,MRUN,KREPL,J,I,
3670      &      IORDER(I,J),INVOH(I,J),INVOR(I,J),IBACKT(I,J),
3680      &      IBAKDT(I,J),IRETRN(I,J),IREQT(I,J),IFILLT(I,J)
3690      301  FORMAT(5I5,8I10)
3700      302  FORMAT(IH1, 'IDENT MRUN REP J QTR '
3710      &      T30, 'IORDER',T40, 'INVOH',T50, 'INVOR',T60, 'IBACKT',
3720      &      T70, 'IBAKDT',T80, 'IRETRN',T90, 'IREQT',T100, 'FILLT'
3730      232  CONTINUE
3740      233  CONTINUE
3750      R=(ITIME-800)/ITYEAR+1
3760      NPLOT=1
3770      WRITE(6,8333)NPLOT,R
3780      WRITE(6,8330)
3790      WRITE(6,8332) (I,PX(I),(PY(I,J),J=1,4),I=1,IPLLOT)
3800      GO TO 99
3810      31  CONTINUE
3820      C      SPECIAL STATISTICS
3830      CALL SSTAT(IP3)
3840      GO TO 20
3850      32  CONTINUE
3860      C      DEMAND PARAMETER UPDATE
3870      CALL DEMPAR(IP3,IP4,IP5)
3880      GO TO 20
3890      33  CONTINUE
3900      IF(ITIME.GT.ISTRAC) GO TO 332
3910      C      RECORD HISTORY FOR ITEM NPLLOT
3920      IPLLOT=IPLLOT+1
3930      PX(IPLLOT)=ITIME
3940      PY(IPLLOT,1)=INVACT(1)
3950      PY(IPLLOT,2)=INVDUE(1)
3960      PY(IPLLOT,3)=NBOTU(1)
3970      PY(IPLLOT,4)=IOBLIG
3980      IF(IPLLOT.LT.48) GO TO 331
3990      R=(ITIME-800)/ITYEAR+1
4000      WRITE(6,8333)NPLLOT,R
4010      WRITE(6,8332) (I,PX(I),(PY(I,J),J=1,4),I=1,IPLLOT)
4020      8330  FORMAT(//11X,4H WEEK,11X,4H TIME,8X,7H ON-HAND,9X,6H DUE-IN,30
4030      C-ORDERED //)
4040      8332  FORMAT(52(6I15//))
4050      8333  FORMAT(IH1//20X,22H STOCK HISTORY FOR ITEM,15,10X,5H YEAR=,5
4060      IPLLOT=0
4070      C

```



p. 9 of 9

```

4080 C      WRITE BACKORDER FILE
4090 C
4100      IF(IDBUG.NE.1) GO TO 331
4110      DO 298 N=1,NITEM
4120      IF(NBOPT(N).LE.0) GO TO 298
4130      JPT=NBOPT(N)
4140      288 CONTINUE
4150      I=JPT
4160      WRITE(6,8444)I,IDFSNB(I),IQTYB(I),IPRIOR(I),ITMBAC(I),IBAC
4170      8444 FORMAT(I10,5I8)
4180      IF(IBACPT(JPT).EQ.0) GO TO 298
4190      JPT=IBACPT(JPT)
4200      GO TO 288
4210      298 CONTINUE
4220      331 CONTINUE
4230      INEXT=ITIME+ITWEEK
4240      CALL ENTER(INEXT,13,0,0,IPL0T)
4250      GO TO 20
4260 C
4270 C      TURN OFF DEBUG SWITCH (IDBUG)
4280 C
4290      332 IDBUG=0
4300      GO TO 20
4310      34 CONTINUE
4320      35 CONTINUE
4330      36 CONTINUE
4340      37 CONTINUE
4350      38 CONTINUE
4360      39 CONTINUE
4370 C      KTYPE OUT OF RANGE-WRITE ERROR MESSAGE
4380      WRITE(6,113) KTYPE
4390      113 FORMAT(IH1,2IH***ERROR***      KTYPE=,13,3X,12HOUT OF RANGE)
4400      STOP
4410 C
4420 C      END OF LOOP
4430 C
4440      95 CONTINUE
4450      99 CONTINUE
4460      GO TO 10
4470      9999 CONTINUE
4480      9998 FORMAT(///// '****MAIN--END OF FILE 05')
4490      STOP
4500      END
4510 $      ENDJOB
4520 C

```

Subroutine: ORDER

Function:

This routine performs the bookkeeping tasks required to reflect the placement of an order to replenish existing stocks, and to schedule the receipt of an order.

Description:

Subroutine ORDER first enters a type 2 event (receipt) onto the Future Events List. This will cause a receipt for IBQ units of item N a leadtime into the future. Next, ORDER updates the variables IOBLIG and INVDUE(N) which record the dollar values of obligations within the current budget period and the total number of units on order for item N, respectively. Performance variables IBOPSM and IBOPLG are next updated to reflect any small or large purchases which are placed in the initial quarter of the simulation. Finally, subroutine ORDER updates the pointer NORDPT(N) which points from item N to the corresponding receipt event on the Future Events List.

```

20      $      IDENT      WP#287,ADDSC-CALLAHAN
30      $      FORTY      DECK
40      $      PRMFL      C*,W,S,REQS/ORDER.0
50      $      REMOTE      P*,AC
60      $      REMOTE      $$,AC
70      SUBROUTINE ORDER(N,IBQ,JTIME)
80      C          THIS ROUTINE UPDATES STATISTICS TO REFLECT AN ORDER FORM
90      C          UNITS OF ITEM N, WITH DELIVERY DATE SCHEDULED FOR JTIME
100     C          PLACES THE ASSOCIATED RECEIPT TRANSACTION ON THE FUTURE
110     C          LIST.
120     COMMON/IDBUG/IDBUG
130     COMMON/IOBLIG/IOBLIG
140     COMMON/NLOC/NLOC
150     COMMON/CSTBRK/CSTBRK
160     COMMON/ISMORD/ISMORD(30,3)
170     COMMON/ILGORD/ILGORD(30,3)
180     COMMON/IORDER/IORDER(30,3)
190     COMMON/NORDPT/NORDPT(50)
200     COMMON/INVDUE/INVDUE(50)
210     COMMON/UCOST/UCOST(50)
220     COMMON/JPRIOR/JPRIOR(500)
230     COMMON/ITIME/ITIME
240     COMMON/IBOPCT/IBOPSM(3),IBOPLG(3)
250     C          PLACE ORDER FOR IBQ UNITS
260     CALL ENTER(JTIME,2,N,IBQ,0)
270     NPPT=NORDPT(N)
280     C          UPDATE STATUS STATISTICS
290     IOBLIG=FLOAT(IOBLIG)+FLOAT(IBQ)*UCOST(N)
300     INVDUE(N)=INVDUE(N)+IBQ
310     DVORD=FLOAT(IBQ)*UCOST(N)
320     IF(ITIME .LE. 0) GO TO 100
330     CALL CUM(IORDER,IBQ,N)
340     DVORD=FLOAT(IBQ)*UCOST(N)
350     IF(DVORD .GE. CSTBRK) CALL CUM(ILGORD,IBQ,N)
360     IF(DVORD .LT. CSTBRK) CALL CUM(ISMORD,IBQ,N)
370     GO TO 200
380     100     IDVORD=IFIX(DVORD)
390     IF(DVORD .GE. CSTBRK) GO TO 150
400     IBOPSM(1)=IBOPSM(1) + 1
410     IBOPSM(2)=IBOPSM(2) + IBQ
420     IBOPSM(3)=IBOPSM(3) + IDVORD
430     GO TO 200
440     150     IBOPLG(1)=IBOPLG(1) + 1
450     IBOPLG(2)=IBOPLG(2) + IBQ
460     IBOPLG(3)=IBOPLG(3) + IDVORD
470     200     CONTINUE
480     C          ARE ANY OTHER ORDERS OUTSTANDING ON THIS ITEM
490     IF(NORDPT(N).GT.0) GO TO 11
500     JPRIOR(NLOC)=0
510     GO TO 12
520     C          UPDATE ORDER REFERENCE DATA
530     11 JPRIOR(NLOC)=NORDPT(N)
540     C          SET ORDER POINTER

```

ORDER (CONT)

p. 2 of 2

```
550      12 NORDPT(N)=NLOC
560      IF(IDBUG.NE.1) GO TO 20
570      WRITE(6,8000)N,IBQ,NORDPT(N),NPPT,NLOC
580      8000 FORMAT(7H ORDER ,I26,7I8)
590      20 CONTINUE
600      RETURN
610      END
620 $      ENDJOB
```

Subroutine: OUT

Function:

This routine produces a report of performance statistics which summarize results for the entire simulation run.

Description:

Subroutine OUT first updates the variables INVOH (I,1) and INVDAY (I,1) to record last quarter statistics, that is, results for period ITINV.

Subroutine OUT then produces 9 summary tables which describe the quarter by quarter activity observed during the simulation run. The tables appear in three separate formats, and each format is repeated with the performance statistics reported in terms of the number of actions that occurred, the number of units effected, and the total dollar value of these units, respectively.

At the bottom of each table the average per year for the simulation is printed. This value is obtained by totalling the quarter by quarter results within the same column, and dividing this total by the number of years that were simulated.

OUT

p. 1 of 4

```
20      $      IDENT      WP0287,ADDSC-CALLAHAN
30      $      FORTY      DECK
40      $      PRMFL      C*,W,S,REQS/OUT.0
50      $      REMOTE      P*,AC
60      $      REMOTE      $$,AC
70      C      SUBROUTINE OUT
80      SUBROUTINE OUT
90      DIMENSION ITOTL(23,3),AVEVR(23)
100     COMMON/INQTR/INQTR
110     COMMON/ITIME/ITIME
120     COMMON/ITYEAR/ITYEAR
130     COMMON/ITINV/ITINV
140     COMMON/INVACT/INVACT(50)
150     COMMON/NDENT/NDENT(50)
160     COMMON/NREPL/NREPL
170     COMMON/NITEM/NITEM
180     COMMON/IBOP/IBOP(3),IBOPOR(3)
190     COMMON/IBACKI/IBACKI(30,3)
200     COMMON/IBACKT/IBACKT(30,3)
210     COMMON/IBAKDI/IBAKDI(30,3)
220     COMMON/IBAKDT/IBAKDT(30,3)
230     COMMON/ICANCL/ICANCL(30,3)
240     COMMON/IDISPS/IDISPS(30,3)
250     COMMON/IEXPED/IEXPED(30,3)
260     COMMON/IFILLI/IFILLI(30,3)
270     COMMON/IFILLT/IFILLT(30,3)
280     COMMON/IORDER/IORDER(30,3)
290     COMMON/INVDAY/INVDAY(30,3)
300     COMMON/INVOH/INVOH(30,3)
310     COMMON/INVOR/INVOR(30,3)
320     COMMON/IRATON/IRATON(30,3)
330     COMMON/IRECET/IRECET(30,3)
340     COMMON/IREQC /IREQC(30,3)
350     COMMON/IREQI /IREQI(30,3)
360     COMMON/IREQT/IREQT(30,3)
370     COMMON/IRETRN/IRETRN(30,3)
380     COMMON/ISHIPI/ISHIPI(30,3)
390     COMMON/ISHIPT/ISHIPT(30,3)
400     COMMON/ITERM /ITERM(30,3)
410     C
420     C      TIDY UP LAST PERIOD STATISTICS
430     C
```



OUT (CONT)

p. 2 of 4

```

440      I=ITINV
450      INVDAY(I,1)=0
460      INVVOH(I,1)=0
470      DO 500 N=1,NITEM
480      IF(NDENT(N).LT.0) GO TO 500
490      INVVOH(I,1)=INVVOH(I,1)+1
500      IF(INVACT(N).LE.0) GO TO 500
510      INVDAY(I,1)=INVDAY(I,1)+1
520      500 CONTINUE
530      R=FLOAT(ITIME)/FLOAT(ITVEAR)
540      C
550      RN=R/FLOAT(NITEM)/FLOAT(NREPL)
560      DO 201 I=1,23
570      DO 201 J=1,3
580      AVEVR(I)=0.
590      201 ITOTL(I,J)=0
600      J=1
610      2 CONTINUE
620      ASSIGN 41 TO ISW
630      1 IF(J.GT.3) GO TO 900
640      WRITE(6,100)
650      WRITE(6,102)
660      WRITE(6,103)
670      WRITE(6,102)
680      GO TO(10,20,30),J
690      10 WRITE(6,104)
700      GO TO 40
710      20 WRITE(6,106)
720      GO TO 40
730      30 WRITE(6,107)
740      40 GO TO ISW,(41,51,52)
750      41 WRITE(6,105)
760      WRITE(6,108)
770      WRITE(6,109)
780      WRITE(6,110)
790      WRITE(6,121)IBOPOH(J),IBOPOR(J)
800      DO 50 I=1,INGTR
810      ITOTL(1,J)=ITOTL(1,J)+INVVOH(I,J)
820      ITOTL(2,J)=ITOTL(2,J)+INVOR(I,J)
830      ITOTL(3,J)=ITOTL(3,J)+IRECET(I,J)
840      ITOTL(4,J)=ITOTL(4,J)+IRETRN(I,J)
850      ITOTL(5,J)=ITOTL(5,J)+ISHIPT(I,J)
860      ITOTL(6,J)=ITOTL(6,J)+ISHIPI(I,J)
870      ITOTL(7,J)=ITOTL(7,J)+IORDER(I,J)
880      ITOTL(8,J)=ITOTL(8,J)+IREQT(I,J)
890      ITOTL(9,J)=ITOTL(9,J)+IREQC(I,J)
900      ITOTL(10,J)=ITOTL(10,J)+IREQI(I,J)
910      50 WRITE(6,120) I,INVVOH(I,J),INVOR(I,J),IRECET(I,J),IRETRN(I,J),
920      CT(I,J),ISHIPI(I,J),IORDER(I,J),IREQT(I,J),IREQC(I,J),IREQI
930      WRITE(6,110)

```

OUT (CONT)

p. 3 of 4

```

940      WRITE(6,202) (ITOTL(I,J),I=1,10)
950      202 FORMAT(1H0,8H*TOTALS*,110,9(2X,110))
960      DO 203 I=1,10
970      203 AVEVR(I)=FLOAT(ITOTL(I,J))/R
980      WRITE(6,204) (AVEVR(I),I=1,10)
990      204 FORMAT(1H0,6HAVE/VR,1X,10(3X,F9.0))
1000     DO 305 I=1,10
1010     305 AVEVR(I)=FLOAT(ITOTL(I,J))/RN
1020     WRITE(6,306) (AVEVR(I),I=1,10)
1030     306 FORMAT(1H0,6HAVE/IV,1X,10(3X,F9.2))
1040     ASSIGN 51 TO ISW
1050     GO TO 1
1060     51 WRITE(6,111)
1070     WRITE(6,112)
1080     WRITE(6,67)
1090     DO 57 I=1,INQTR
1100     ITOTL(11,J)=ITOTL(11,J)+IEXPED(I,J)
1110     ITOTL(12,J)=ITOTL(12,J)+IRATON(I,J)
1120     ITOTL(13,J)=ITOTL(13,J)+IDISPS(I,J)
1130     ITOTL(14,J)=ITOTL(14,J)+ITERM(I,J)
1140     57 WRITE(6,113) I,IEXPED(I,J),IRATON(I,J),IDISPS(I,J),ITERM(I,J)
1150     WRITE(6,67)
1160     WRITE(6,205) (ITOTL(I,J),I=11,14)
1170     205 FORMAT(1H0,31X,8H*TOTALS*,4(2X,110))
1180     DO 206 I=11,14
1190     206 AVEVR(I)=FLOAT(ITOTL(I,J))/R
1200     WRITE(6,207) (AVEVR(I),I=11,14)
1210     207 FORMAT(1H0,33X,7HAVE/VR,4(3X,F9.0))
1220     DO 315 I=11,14
1230     315 AVEVR(I)=FLOAT(ITOTL(I,J))/RN
1240     WRITE(6,316) (AVEVR(I),I=11,14)
1250     316 FORMAT(1H0,33X,6HAVE/IV,4(3X,F9.2))
1260     ASSIGN 52 TO ISW
1270     GO TO 1
1280     52 WRITE(6,114)
1290     WRITE(6,115)
1300     WRITE(6,116)
1310     WRITE(6,68)
1320     DO 58 I=1,INQTR
1330     IF(IREQT(I,J).LE.0) GO TO 62
1340     T1=FLOAT(IFILLT(I,J))/FLOAT(IREQT(I,J))
1350     GO TO 63
1360     62 T1=0.
1370     63 CONTINUE
1380     IF(IREQI(I,J).LE.0) GO TO 64
1390     T2=FLOAT(IFILLI(I,J))/FLOAT(IREQI(I,J))
1400     GO TO 65
1410     64 CONTINUE
1420     T2=0.
1430     65 CONTINUE
1440     ITOTL(15,J)=ITOTL(15,J)+IBACKT(I,J)
1450     ITOTL(16,J)=ITOTL(16,J)+IBACKI(I,J)

```

OUT (CONT)

p. 4 of 4

```

1460      ITOTL(17,J)=ITOTL(17,J)+IBAKDT(I,J)
1470      ITOTL(18,J)=ITOTL(18,J)+IBAKDI(I,J)
1480      ITOTL(19,J)=ITOTL(19,J)+INVDAY(I,J)
1490      ITOTL(20,J)=ITOTL(20,J)+IFILLT(I,J)
1500      ITOTL(21,J)=ITOTL(21,J)+IFILLI(I,J)
1510      58 WRITE(6,117) I,IBAKT(I,J),IBACKI(I,J),IBAKDT(I,J),IBAKDI(I,J),
1520      CINVDAY(I,J),IFILLT(I,J),IFILLI(I,J),T1,T2
1530      WRITE(6,68)
1540      WRITE(6,208) (ITOTL(I,J),I=15,21)
1550      203 FORMAT(1H0,8X,8H*TOTALS*,1X,7(1H0,2X))
1560      DO 209 I=15,21
1570      209 AVEYR(I)=FLOAT(ITOTL(I,J))/R
1580      AVEYR(22)=FLOAT(ITOTL(20,J))/FLOAT(ITOTL(8,J))
1590      AVEYR(23)=FLOAT(ITOTL(21,J))/FLOAT(ITOTL(10,J))
1600      210 FORMAT(1H0,9X,7HAVE/YR,7F12.0,2F14.3)
1610      WRITE(6,210) (AVEYR(I),I=15,23)
1620      DO 325 I=15,23
1630      325 AVEYR(I)=FLOAT(ITOTL(I,J))/RN
1640      WRITE(6,329) (AVEYR(I),I=15,23)
1650      329 FORMAT(1H0,9X,6HAVE/YR,7F12.2,2F14.3)
1660      J=J+1
1670      GO TO 2
1680      67 FORMAT(1H,35X,2H--,2X,4(12H -----))
1690      68 FORMAT(1H,11X,2H--,2X,7(12H -----),2(14H -----)
1700      100 FORMAT(1H1,/,/,/,/)
1710      101 FORMAT(1H,/,/)
1720      102 FORMAT(1H,43X,44(1H-))
1730      103 FORMAT(1H,43X,44HP E R F O R M A N C E   S T A T I S T I C
1740      104 FORMAT(1H,/,/,54X,25H*** ACTIONS/FSN@S ***,/ )
1750      105 FORMAT(1H0,69X,10HPRIORITY 1)
1760      107 FORMAT(1H,/,/,56X,10H$$$ DOLLARS $$$)
1770      106 FORMAT(1H,/,/,56X,17H... UNITS ...)
1780      108 FORMAT(1H,10X,21HINVENTORY INVENTORY,28X,67HTOTAL
1790      C ORDERS TOTAL REGS PRIORITY 1)
1800      109 FORMAT(1H,128HPERIOD ON HAND ON ORDER RECEIPTS
1810      CNS SHIPMENTS SHIPMENTS PLACED REQUISITIONS CA
1820      CEGUISITIONS)
1830      110 FORMAT(1H,2X,2H--,2X,10(4X,8(1H-)))
1840      111 FORMAT(1H0,54X,9HRATIONING)
1850      112 FORMAT(1H,33X,57HPERIOD EXPEDITES ACTIONS DISPO
1860      CMINATIONS)
1870      113 FORMAT(1H,35X,12,2X,4(4X,18))
1880      114 FORMAT(1H0,44X,20HTOTAL PRIORITY 1)
1890      115 FORMAT(1H,20X,108HTOTAL PRIORITY 1 BACKORDER BACKO
1900      C INVENTORY TOTAL PRIORITY 1 TOT FILLS PRI 1 F
1910      116 FORMAT(1H,9X,120HPERIOD BACKORDERS BACKORDERS DAYS
1920      C DAYS DAYS FILLS FILLS /TOT REG
1930      C REGS)
1940      117 FORMAT(1H,11X,12,2X,7(4X,18),2(4X,F10.2))
1950      120 FORMAT(1H,2X,12,2X,10(4X,18))
1960      121 FORMAT(1H,1X,3HBOP,2X,2(4X,18))
1970      999 RETURN
1980      END
1990

```

Subroutine: OUTCST

Function:

This routine prints a summary of ordering activity observed during the simulation run.

Description:

This routine prints a summary table describing the number of order actions taken, the number of units effected, and the total dollar value of these orders. The results are segregated in terms of "small ordering actions" and "large ordering actions". A small ordering action is defined as an order whose total dollar value is less than CSTBRK dollars.

Finally, subroutine OUTCST prints averages per year of each of the statistics presented.

OUTCST  
p. 1 of 2

```

SUBROUTINE OUTCST
COMMON/NITEM/NITEM
COMMON/NREPL/NREPL
COMMON/INQTR/INQTR
COMMON/ISMORD/ISMORD(30,3)
COMMON/ILGORD/ILGORD(30,3)
COMMON/COSORD/COSORD(3)
COMMON/IBOPCT/IBOPSM(3),IBOPLG(3)
COMMON/CSTBRK/CSTBRK
DIMENSION IDUM(3),ITOT(9)
LW=6
CORDSM=COSORD(1)
CORDLG=COSORD(2)
DO 1 I=1,9
1 ITOT(I)=0
WRITE(LW,100)
WRITE(LW,200)
WRITE(LW,800) CORDSM,CORDLG
WRITE(LW,300)
IDUM(1)=IBOPSM(1) + IBOPLG(1)
IDUM(2)=IBOPSM(2) + IBOPLG(2)
IDUM(3)=IBOPSM(3) + IBOPLG(3)
WRITE(LW,700) IBOPSM,IBOPLG,IDUM
DO 2 I=1,INQTR
DO 3 J=1,3
K=J + 3
L=J + 6
IDUM(J)=ISMORD(I,J) + ILGORD(I,J)
ITOT(J)=ITOT(J) + ISMORD(I,J)
ITOT(K)=ITOT(K) + ILGORD(I,J)
3 ITOT(L)=ITOT(L) + IDUM(J)
2 WRITE(LW,400) I,(ISMORD(I,J),J=1,3),(ILGORD(I,K),K=1,3),IDUM
WRITE(LW,500) ITOT
TOTSM=FLOAT(ITOT(1))*CORDSM
TOTLG=FLOAT(ITOT(4))*CORDLG
TOT=TOTSM + TOTLG
WRITE(LW,600) TOTSM,TOTLG,TOT
WRITE(LW,900) CSTBRK
RN=FLOAT(NITEM*NREPL)
TOTSM=TOTSM/RN
TOTLG=TOTLG/RN
TOT=TOTSM+TOTLG
WRITE(LW,605)
605 FORMAT(/T10,'AVERAGE COST/ITEM/YR')
WRITE(LW,600)TOTSM,TOTLG,TOT
100 FORMAT(1H1,4X,'***** ORDER COST STATISTICS *****')
200 FORMAT(1H0,'TIME',10X,'SMALL ORDERS',18X,'LARGE ORDERS',18X,'TOTAL
1 ORDERS')
300 FORMAT(1H0,3X,3(4X,'NUMBER UNITS DOLLARS'))
400 FORMAT(1H ,12,4X,3(I6,I10,I10,4X))
500 FORMAT(1H0,'TOTALS',1X,3(I6,I10,I10,4X))
600 FORMAT(1H0,'SMALL ORDER COST ',E15,8,' PLUS LARGE ORDER COST ',E15

```



01 04-16-77 12.087

OUTCST

p. 2

```
1.8, ' EQUALS TOTAL ORDER COST ', E15.8)
700 FORMAT(1H0, 'BOP', 4X, 3(I6, I10, I10, 4X))
800 FORMAT(1H0, 'COST TO ORDER', 4X, F6.2, 24X, F6.2)
900 FORMAT(1H0, 'EOQ BUY DOLLAR BREAK POINT ', F10.2)
RETURN
END
```



Subroutine: PLOTR

Function:

This routine plots performance statistics verses time for several performance measures.

Description:

This routine calls subroutine GP to produce four separate types of plots. These are:

- a. Requisitions, cancellations, and disposals by quarter.
- b. On-hand, on-order, and backordered stock by quarter. Aggregate pipeline stock is also plotted, where aggregate stock equals on-hand plus on-order stocks.
- c. Requisitions, fills, backorders, and cancellations by quarter.
- d. Cumulative budgeted expenditures and cumulative obligations (i.e., dollar value of orders placed) by quarter.

```

SUBROUTINE PLOT
COMMON /INVGH/INVGH(30,3)
COMMON /INVGR/INVGR(30,3)
COMMON /IBACKI/IBACKI(30,3)
COMMON /ICANCE/ICANCE(30,3)
COMMON /IDISPS/IDISPS(30,3)
COMMON /IREFT/IREFT(30,3)
COMMON /IFILL/IFILL(30,3)
COMMON /IREFC/IREFC(30,3)
COMMON /IRAUTH/IRAUTH(12)
COMMON /IORIE/IRORDER(30,3)
DIMENSION X(31),Y(31,4),PLT(50,100),A(4)
DIMENSION RMEAS(3)
DATA (RMEAS(I),I=1,3)/6HFSNS ,6HUNITS ,6HDOLLRS/
DATA CH/10H/,CO/10H/,CR/10H/,CA/10H/,CR/10H/,CF/10H/,CC/10H/
DATA CD/10H/
X(31)=0.
DO 5 I=1,4
5 Y(31,I)=0.
A(1)=CP
A(2)=CC
A(3)=CD
DO 110 J=1,3
WRITE(6,3)
WRITE(6,8006) RMEAS(J)
WRITE(6,8040)
8040 FORMAT(10X,16HREQUISITIONS = R,5X,17HCANCELLATIONS = C,5X,13HDISPO
1SAIS = 0)
DO 105 I=1,30
X(I)=FLOAT(I)
Y(I,1)=FLOAT(IREFT(I,J))
Y(I,2)=FLOAT(ICANCE(I,J))
Y(I,3)=FLOAT(IDISPS(I,J))
105 CONTINUE
CALL GP(X,Y,0,16,31,3,100,40,A,PLT)
110 CONTINUE
A(1)=CH
A(2)=CO
A(3)=CR
A(4)=CA
DO 10 J=1,3
DO 20 I=1,30
Y(I,1)=FLOAT(INVGH(I,J))
Y(I,2)=FLOAT(INVGR(I,J))
Y(I,3)=FLOAT(IBACKI(I,J))
20 Y(I,4)=FLOAT(INVGH(I,J))+FLOAT(INVGR(I,J))
WRITE(6,3)
WRITE(6,8010)
WRITE(6,8000)RMEAS(J)
8010 FORMAT(10X,11HON-HAND = R,5X,12HON-ORDER = 0,5X,14HBACKORDERS = R,
15X,13HAGGREGATE = A)
10 CALL GP(X,Y,0,16,31,4,100,40,A,PLT)

```

02-11-77 10.691

PLDTR,  
p. 2

```

A(1)=CR
A(2)=CF
A(3)=CR
A(4)=CC
DO 30 J=1,3
Y(1,1)=FLOAT(IREOT(1,J))
Y(1,2)=FLOAT(IFILT(1,J))
Y(1,3)=FLOAT(IRACKT(1,J))
Y(1,4)=FLOAT(ICANCEL(1,J))
DO 40 I=2,30
Y(I,1)=FLOAT(IREOT(I,J))+Y(I-1,1)
Y(I,2)=FLOAT(IFILT(I,J))+Y(I-1,2)
Y(I,3)=FLOAT(IRACKT(I,J))+Y(I-1,3)
40 Y(I,4)=FLOAT(ICANCEL(I,J))+Y(I-1,4)
WRITE (6,3)
WRITE(6,8020)
WRITE(6,8000)RMELAS(J)
8020 FORMAT(10X,16HREQUISITIONS = P,5X,9HFILLS = F,5Y,14HBACKORDERS = B
1,5X,17HCANCELLATIONS = C)
30 CALL GP(X,Y,0,16,31,4,100,40,A,PLT)
A(1)=CR
A(2)=CC
I=3
Y(1,1)=FLOAT(IRATH(1))
Y(1,2)=FLOAT(10ORDER(1,J))
DO 60 I=2,30
KK=((I-1)/4)+1
IBI=0
DO 74 K=1,KK
70 IRI=IRI+IRATH(K)
Y(I,1)=FLOAT(IRI)
60 Y(I,2)=FLOAT(10ORDER(I,J))+Y(I-1,2)
WRITE (6,5)
WRITE(6,8030)
WRITE(6,8000)RMELAS(J)
8030 FORMAT(10X,10HBUGFI = B,5X,10HORDERS = O)
50 CALL GP(X,Y,0,16,31,2,100,40,A,PLT)
3 FORMAT('1')
8000 FORMAT('0', 'MEASURED IN ...',A6)
RETURN
END

```

Subroutine: RANDU

Function:

This routine generates uniformly distributed random numbers on the interval 0. to 1.0.

Description:

This routine uses the congruential method to generate pseudo-random numbers. A call of the form

CALL RANDU (X)

where X is negative, causes the random number seed to be set to the absolute value of X. If X is positive, X has no effect on the calculation.

RANDU  
p 1 of 1

92-11-77 10.717

RANDU--U(0,1) RANDOM NUMBER GENERATOR.

```
C      RANDU--U(0,1) RANDOM NUMBER GENERATOR.
      FUNCTION RANDU(X)
C      A CALL WITH X < 0. INITIALIZES THE RANDOM NUMBER STREAM.
      IF(X) 10,20,20
20  RN=RND*RANDU
      RN1=AMOD(RN,RN)
      RANDU=RN1/RN
      RETURN
10  RND=7.0**13
      RN=10.0**10
      RANDU=-X
      GO TO 20
      END
```

Subroutine: RECEIV

Function:

This routine updates stock status records to reflect the receipt of a replenishment order (event type 2) from a supplier of inventory system.

Description:

This routine updates stock status records to reflect the receipt of an order for IQTY units of item N during the current period. The routine then initiates shipment actions to fill any outstanding backorders.

By convention, order histories are maintained for each item in the form of a string-list ordered from the newest to the oldest outstanding order. When an outstanding order is received, this string must be updated to drop the last element on the string (orders are assumed not to cross). The variable NORDPT (N) indicates the position in the Future Events List of the most recent order for item N. Beginning with this record, the routine searches down the order string to locate the oldest order. The last record on this string is the oldest order placed.

By convention, orders are terminated by setting the order quantity to zero and removing the order transaction from the Future Events List at the regular due-in time.



```

SUBROUTINE RECEIV(N,IQTY)
C   THIS ROUTINE UPDATES STOCK STATUS RECORDS TO REFLECT RECEIPT
C   OF AN ORDER FOR IQTY UNITS OF ITEM N DURING PERIOD I.
C   THE ROUTINE THEN INITIATES SHIPMENT ACTIONS TO FULFILL
C   OUTSTANDING BACKORDERS IF ANY.
COMMON/IDBUG/IDBUG
COMMON/NLOCBK/NLOCBK
COMMON/IRECET/IRECET(30,3)
COMMON/ISHIPT/ISHIPT(30,3)
COMMON/ISHIPT/ISHIPT(30,3)
COMMON/JPRIOR/JPRIOR(500)
COMMON/IQTYB/IQTYB(200)
COMMON/IPRIOR/IPRIOR(200)
COMMON/NBOTU/NBOTU(50)
COMMON/ILOCBK/ILOCBK(200)
COMMON/NORDPT/NORDPT(50)
COMMON/INVACT/INVACT(50)
COMMON/INVDUE/INVDUE(50)
COMMON/NBOPT/NBOPT(50)
COMMON/ISUL/ISUL(50)
COMMON/IBACPT/IBACPT(200)

C   ---NOTE---
C   BY CONVENTION ORDER HISTORIES ARE MAINTAINED FOR EACH ITEM IN
C   THE FORM OF A STRING LIST ORDERED FROM THIS NEWEST TO THE
C   OLDEST OUTSTANDING ORDER. WHEN AN OUTSTANDING ORDER IS RECEIVED,
C   THIS STRING MUST BE UPDATED TO DROP THE LAST ELEMENT ON THE
C   STRING (ORDERS ARE ASSUMED NOT TO CROSS), THE NEXT FEW STATEMENT
C   ACCOMPLISH THIS UPDATE.
NPT=NORDPT(N)
C   IS THIS THE ONLY OUTSTANDING ORDER FOR THIS ITEM
IF(JPRIOR(NPT).NE.0) GO TO 10
C   SET POINTS TO INDICATE THERE IS NO LONGER AN OUTSTANDING ORDER
NORDPT(N)=0
GO TO 15
C   SET POINTERS TO SEARCH DOWN ORDER STRING
10 NPP=NPT
NPT=JPRIOR(NPP)
C   IS NPT THE OLDEST OUTSTANDING ORDER
IF(IDBUG.NE.1) GO TO 12
WRITE(6,991)NPP,NPT
12 CONTINUE
991 FORMAT(1H ,13HLOOP ENTERED=,7HJPRIOR=,14,4HNPT=,12)
IF(JPRIOR(NPT).NE.0) GO TO 10
C   THEN NPT IS THE ORDER JUST RECEIVED, REMOVE THE RECORD FROM THE
C   END OF THE ORDER STRING
JPRIOR(NPP)=0
C   BY CONVENTION ORDERS ARE TERMINATED BY SETTING THE ORDER
C   QUANTITY TO ZERO AND REMOVING THE ORDER TRANSACTION FROM THE
C   FUTURE EVENTS LIST AT THE REGULAR DUE-IN TIME.
C   HAS THIS ORDER BEEN TERMINATED.
15 IF(IQTY.EQ.0) RETURN

```

01 04-16-77 12.090

RECEIV, p. 2 of 2

```
C      ADJUST GROSS RECEIPT STATISTICS
      JQTY=-IQTY
      CALL CUM(IQTY,N)
C      ADJUST ASSETS FOR THIS ITEM
      INVACT(N)=INVACT(N)+IQTY
      INVDUE(N)=INVDUE(N)-IQTY
C      ARE THERE ANY BACKORDERS ON THIS ITEM.
      IF(NBOPT(N).LE.0) RETURN
      CALL FILLBO(N)
      RETURN
      END
```

Subroutine:    REMOVE

Function:

This routine removes the earliest transaction from the Future Events List, and updates the chain list structure.

Description:

This routine determines the "current" event to be simulated within INSSIM. For a detailed description of the event bookkeeping process, see Volume I, Chapter IV.

02-11-77 14.596

REMOVE

p. 1 of 1

```
SUBROUTINE REMOVE(KTIME,KTYPE,KESN,KQTY,KPRIOR)
C      THIS ROUTINE REMOVES THE EARLIEST TRANSACTION FROM THE
C      CURRENT EVENT CHAIN, AND UPDATES THE CHAIN STRUCTURE
COMMON/IDBUG/IDBUG
COMMON/NENTRY/NENTRY
COMMON/NFIRST/NFIRST
COMMON/NTIME/NTIME
COMMON/LOCFF/LOCFF(500)
COMMON/JESN/JESN(500)
COMMON/JPOINT/JPOINT(500)
COMMON/JPRIOR/JPRIOR(500)
COMMON/JQTY/JQTY(500)
COMMON/JTIME/JTIME(500)
COMMON/JTYPE/JTYPE(500)
K=NFIRST
KTIME=JTIME(K)
KTYPE=JTYPE(K)
KESN=JESN(K)
KQTY=JQTY(K)
KPRIOR=JPRIOR(K)
NFIRST=JPOINT(K)
NTIME=JTIME(NFIRST)
IF(IDBUG.NE.1) GO TO 25
WRITE(6,8000)KTIME,KTYPE,KESN,KQTY,KPRIOR,K
8000  FORMAT(7H REMOVE,110,518)
25  CONTINUE
C      IS THIS THE LAST TRANSACTION ON THE LIST
IF(NENTRY.GT.1) GO TO 19
C      SET LIST CLOCK UP A LARGE INCREMENT
NTIME=9999999
C      RECORD LOCATION K AS AVAILABLE
19  LOCFF(NENTRY)=K
C      DECREMENT COUNT OF LIST ENTRIES
NENTRY=NENTRY-1
RETURN
END
```

AD-A046 053

DECISION SYSTEMS DAYTON OH  
THE INVENTORY SYSTEM SIMULATOR (INSSIM). VOLUME II PROGRAM LIST--ETC(U)  
AUG 77 W S DEMMY

F/G 15/5

F49620-77-C-0063

UNCLASSIFIED

RM-77-03


AFOSR-TR-77-1235

NL

2 OF 2  
ADA  
046053



END  
DATE  
FILMED  
12-77  
DDC



1.0

2.8

2.5

5.0

3.15

2.2

5.6

3.5

2.0



1.1


6.3

4.0

1.8

7.1

4.5



1.25



1.4



1.6



Subroutine: REQ

Function:

This routine reflects the receipt of a customer requisition (event type 1), and associated shipping and/or backorder actions.

Description: This routine is called a statement of the form

CALL REQ (N, IQTY, IPRI, LTIME)

Where

N = item number associated with the current requisition event

IQTY = quantity associated with this requisition

IPRI = the priority of the requisition, where IPRI = 1 denotes a high priority requisition, and IPRI = 2 denotes a low priority requisition

LTIME = the time of receipt of the current requisition

First, the subroutine REQ updates the accumulators NDEMAC (N) and NREQAC (N). Next, the routine attempts to ship on hand assets to fill this requisition. For low priority requisitions (i.e. requisitions with a priority code = 2) units are shipped until on hand stock reaches the support level for the item. For high priority requisitions, shipments are made until on hand stock is reduced to zero.

If there is insufficient stock to completely satisfy the requisition, subroutine ENTERB is called to record a backorder for this item.

At the conclusion of the routine, subroutine CUM is called to update shipping and fillrate statistics.

REQ, p. 1 of 2

```

SUBROUTINE REQ(N,IQTY,IPRI,LTIME)
C   THIS ROUTINE REFLECTS PROCESSING OF A REQUISITION FOR IQTY
C   UNITS OF ITEM N DURING PERIOD I, WHERE IPRI=1 DENOTES A HIGH
C   PRIORITY REQUISITION; IPRI=2 DENOTES A LOW PRIORITY REQUISITION
C   JTIME DENOTES THE CLOCK TIME THE REQ WAS RECEIVED
C   RECORD REQUISITION DATA
COMMON/REQSIZ/REQSIZ(50)
COMMON/REQMAD/REQMAD(50)
COMMON/NDEMAC/NDEMAC(50)
COMMON/NREQAC/NREQAC(50)
COMMON/IREQT/IREQT(30,3)
COMMON/IREQT/IREQT(30,3)
COMMON/INVACT/INVACT(50)
COMMON/ISUL/ISUL(50)
COMMON/ISHIRI/ISHIRI(30,3)
COMMON/ISHIRT/ISHIRT(30,3)
COMMON/IFILLT/IFILLT(30,3)
COMMON/IFILLI/IFILLI(30,3)
COMMON/NBOTU/NBOTU(50)
CALL CUM(IREQT,IQTY,N)
C   IS THIS A PRIORITY 1 REQ
IF(IPRI.NE.1) GO TO 20
CALL CUM(IREQT,IQTY,N)
C   UPDATE DEMAND ACCUMULATOR AND EXPONENTIALLY SMOOTHED
20 NDEMAC(N)=NDEMAC(N)+IQTY
NREQAC(N)=NREQAC(N)+1
C   IS THERE ANY STOCK ON HAND
IF(INVACT(N).GT.0) GO TO 40
PUT THIS REQUISITION IN BACKORDER STATUS
CALL ENTERB(N,IQTY,IPRI,LTIME)
C   UPDATE BACKORDER STATISTICS
NBOTU(N)=NBOTU(N)+IQTY
RETURN
C   SET ITESI=STOCK REMAINING IF THE ORDER WERE FILLED COMPLETELY
40 ITEST=INVACT(N)-IQTY
C   IS ITEST ABOVE THE SUPPORT LEVEL
IF(ITEST.GT.ISUL(N)) GO TO 80
C   IS THIS REQ PRIORITY 1
IF(IPRI.NE.1) GO TO 60
C   CAN THE REQUISITION BE COMPLETELY SATISFIED FROM STOCK ON-HAND
IF(INVACT(N).GE.IQTY) GO TO 80
C   SHIP ALL REMAINING ON-HAND STOCK IN PARTIAL SUPPLYMENT
C   OF THIS REQUISITION
IQTYS=INVACT(N)
C   COMPUTE QUANTITY TO BE BACKORDERED AND UPDATE PRI-1 STATS
IBK=IQTY-IQTYS
CALL CUM(ISHIRI,IQTYS,N)
CALL CUM(IFILLI,IQTYS,N)
GO TO 65
C   ARE ON-HAND ASSETS ABOVE THE SUPPORT LEVEL
60 IF(INVACT(N).LE.ISUL(N)) GO TO 70
C   SHIP DOWN TO THE SUPPORT LEVEL

```

```
      IQTYS=INVACT(N)-ISQL(N)
      BACKORDER THE REMAINING QUANTITY
      IBK=IQTY-IQTY
65  CALL ENTERB(N,IBK,IPRI,LTIME)
      C      UPDATE STOCK STATUS RECORDS
      INVACT(N)=INVACT(N)-IQTYS
      NBOTU(N)=NBOTU(N)+IBK
      C      UPDATE GROSS PERFORMANCE STATISTICS
      JQTY=-IQTYS
      CALL CUM(ISHIPT,IQTY,N)
      CALL CUM(IFILLT,IQTY,N)
      RETURN
70  CONTINUE
      C      BACKORDER ENTIRE REQUISITION
      CALL ENTERB(N,IQTY,IPRI,LTIME)
      C      UPDATE STOCK STATUS RECORDS
      C      UPDATE STOCK STATUS RECORDS
      NBOTU(N)=NBOTU(N)+IQTY
      RETURN
      C      SHIP TO FILL THE ENTIRE REQUISITION
80  IQTYS=IQTY
      C      UPDATE THE STOCK STATUS RECORDS
      INVACT(N)=INVACT(N)-IQTYS
      C      UPDATE PERFORMANCE
      JQTY=-IQTYS
      CALL CUM(ISHIPT,IQTY,N)
      CALL CUM(IFILLT,IQTY,N)
      C      IS THIS A PRIORITY 1 REQUISITION
      IF(IPRI.NE.1) GO TO 85
      C      UPDATE PRIORITY 1 STATISTICS
      CALL CUM(ISHIPT,IQTY,N)
      CALL CUM(IFILLT,IQTY,N)
85  CONTINUE
      RETURN
      END
```

Subroutine: RET

Function:

This routine reflects the receipt of serviceable returns by the supply system (event code = 4).

Description:

First, the accumulator NRETAC (N) is updated to reflect the receipt of IQTY units of item N. Next, the performance statistic IRETRN is updated, and onhand assets INVACT (N) are increased. Finally, subroutine FILLBO is called in an attempt to fill any outstanding back-orders.

01 04-16-77 12.093

RET  
p. 1 of 1

```
SUBROUTINE RET(N,IQTY,ITIME)
COMMON/NRETAC/NRETAC(1)
COMMON/IRETRN/IRETRN(30,3)
COMMON/INVACT/INVACT(1)
COMMON/NBOPT/NBOPT(1)
```

```
*
*   UPDATE SERVICEABLE RETURN ACCUMULATOR
*
```

```
NRETAC(N)=NRETAC(N) + IQTY
```

```
*
*   UPDATE AGGREGATE PERFORMANCE STATISTICS
*
```

```
CALL CUM(IRETRN,IQTY,N)
```

```
*
*   UPDATE CURRENT ON-HAND ASSETS FOR ITEM N
*
```

```
INVACT(N)=INVACT(N) + IQTY
```

```
*
*   ARE THERE ANY BACKORDERS ON THIS ITEM
*
```

```
IF(NBOPT(N) .LE. 0) RETURN
```

```
*
*   ELSE REDUCE BACKORDERS BY AMOUNT OF RETURNS
*
```

```
CALL FILLBO(N)
RETURN
END
```



Subroutine: SSTAT

Function:

This routine updates time persistent and end of period statistics.

Description:

This routine is called at the end of each simulation week. Subroutine SSTAT first updates the performance statistics INVDAY, IBAKDT, and IBAKDI. These variables record inventory-weeks and back-order week measures.

At the end of each quarter, the routine computes values for the end of period variables INVOH, INVOR, IVACKT, and IBACKI. These variables record the end of period status for on hand stocks, on order stocks, and total backorders and priority 1 backorders. The period counters KEND (which denotes the week number within the quarter) and ITINV (the current quarter number) are also incremented by one at the end of each quarter.

Finally, this routine ends by entering a new type 11 event onto the Future Events List.



```

20      $      IDENT      WP#287,ADDSC-CALLAHAN
30      $      FORTY      DECK
40      $      PRMFL      C*,W,S,REQS/SSTAT.O
50      $      REMOTE      P*,AC
60      $      REMOTE      $$,AC
70      SUBROUTINE SSTAT(KEND)
80      C      SUBROUTINE SSTAT
90      COMMON/IDSTAT/IDSTAT
100     COMMON/ISTAT/ISTAT
110     COMMON/ISTOP/ISTOP
120     COMMON/ITIME/ITIME
130     COMMON/ITINV/ITINV
140     COMMON/ITQTR/ITQTR
150     COMMON/NITEM/NITEM
160     COMMON/NBMAX/NBMAX
170     COMMON/NLOCBK/NLOCBK
180     COMMON/INVACT/INVACT(50)
190     COMMON/INVDUE/INVDUE(50)
200     COMMON/NDENT/NDENT(50)
210     COMMON/IBACKI/IBACKI(30,3)
220     COMMON/IBACKT/IBACKT(30,3)
230     COMMON/IBAKDT/IBAKDT(30,3)
240     COMMON/IBAKDI/IBAKDI(30,3)
250     COMMON/INVDAY/INVDAY(30,3)
260     COMMON/INVOH/INVOH(30,3)
270     COMMON/INVOR/INVOR(30,3)
280     COMMON/NBOTU/NBOTU(50)
290     COMMON/UCOST/UCOST(50)
300     I = ITINV
310     DO 50 N= 1,NITEM
320     IF(NDENT(N).LE.0) GO TO 50
330     IF(INVACT(N).LE.0)GO TO 20
340     INVDAY(I,1) = INVDAY(I,1) + 1
350     INVDAY(I,2) =INVDAY(I,2) + INVACT(N)
360     INVDAY(I,3) = INVDAY(I,3) + IFIX(UCOST(N)*FLOAT(INVACT(N)))
370     GO TO 50
380     20 CONTINUE
390     IF(NBOTU(N).LE.0)GO TO 50
400     NRS=NBOTU(N)
410     CALL CUMB(IBAKDT,NRS,N)
420     CALL CUMB(IBAKDI,NRS,N)
430     50 CONTINUE
      C

```

```

440      C      UPDATE REQUISITIONS-SHORT COUNT
450      C
460      NRS=NBMAX-NLOCBK
470      IF(NRS.LE.0) GO TO 60
480      IBAKDI(I,1)=IBAKDI(I,1)+NRS
490      IBACKI(I,1)=IBACKI(I,1)+NRS
500      60  CONTINUE
510      C
520      KP = ITQIR/IDSTAT
530      IF(KEND.GE.KP)GO TO 100
540      KEND = KEND + 1
550      GO TO 200
560      C
570      C      UPDATE END OF PERIOD STATISTICS
580      C
590      100  CONTINUE
600      DO 150 N=1,NITEM
610      IF(NDENT(N).LE.0) GO TO 150
620      IF(INVACT(N).GT.0) CALL CUM(INVOH,INVACT(N),N)
630      IF(NBOTU(N).GT.0) CALL CUMB(IBACKT,NBOTU(N),N)
640      IF(NBOTU(N).GT.0) CALL CUMB(IBACKI,NBOTU(N),N)
650      IF(INVDUE(N).GT.0) CALL CUM(INVOR,INVDUE(N),N)
660      150  CONTINUE
670      C
680      C      UPDATE COUNT OF EOP REQUISITIONS SHORT
690      C
700      NRS=NBMAX-NLOCBK
710      IF(NRS.LE.0) GO TO 160
720      IBACKT(I,1)=IBACKT(I,1)+NRS
730      IBACKI(I,1)=IBACKI(I,1)+NRS
740      160  CONTINUE
750      C
760      C      INCREMENT PERIOD COUNTERS
770      C
780      KEND=1
790      ITINV=ITINV+1
800      C
810      C      CREATE NEXT STATISTICS COLLECTION EVENT
820      C
830      200  CONTINUE
840      ISTAT = ISTAT + IDSTAT
850      CALL ENTER(ISTAT,11,KEND,KEND,KEND)
860      RETURN
870      END
880      $      ENDJOB

```

Subroutine: STATUS

Function:

This routine represents a stock status review event (event type 5).

Description:

First, subroutine STATUS calls subroutine STATN (N) for each item N simulated. STATN compares current on hand and on order stocks to the inventory control levels associated with item N. Finally, subroutine STAT enters a new type 5 event on the Future Events List.

04-16-77 12.098

STATUS

p. 1 of 1

```
SUBROUTINE STATUS
COMMON/NITEM,NITEM
COMMON/ITIME,ITIME
COMMON/ISTOCK,ISTOCK,IDSTOC
COMMON/NDENT,NDENT(50)
DO 10 N=1,NITEM
CALL STATN(N)
1457 DO LOOP INDEX N MAY NOT BE REDEFINED IN CALL OR ABNORMAL FUNCTION
10 CONTINUE
IS=ITIME+IDSTOC
CALL ENTER(IS,5,0,0,0)
RETURN
END
```

Subroutine:   STATN

Function:

This routine compares the asset position of item N to its precomputed reorder point, termination, and retention levels. It then initiates buy actions according to the models described in AFLC/ACDRL Working Paper 73, March 1974, by Robert J. Stevens.

Description:

This routine is controlled by the code ICDFOR provided at input through file 05. Eight code values are possible; these are defined in detail in AFLC/ACDRL Working Paper 73.

Basically, each of these alternate computations compare available assets to the reorder level, and initiate ordering actions (using subroutine ORDER) if appropriate. The formulas differ in the types of assets which are added together to compare with the reorder level.

At present, termination and disposal actions are not coded into this routine. Consequently, simulation of termination and disposal policies are not presently possible.



04-16-77 12.102

STATN,  
p. 1 of 3

```
* SUBROUTINE STATN(N)
*   THIS ROUTINE COMPARES THE ASSET POSITION OF ITEM N
*   TO ITS PRECOMPUTED REORDER POINT, AND INITIATES BUYS
*   ACCORDING TO THE MODELS ON SERVICEABLE RETURNS DES, IN FOR576
*
*   COMMON/IDBUG/IDBUG
*   COMMON/ICDFOR/ICDFOR
*   COMMON/ITIME/ITIME
*   COMMON/ITMNTN/ITMNTN
*   COMMON/NBMAX/NBMAX
*   COMMON/NLOCBK/NLOCBK
*   COMMON/INVACT/INVACT(50)
*   COMMON/INVDUE/INVDUE(50)
*   COMMON/IROL/IROL(50)
*   COMMON/IRQTY/IRQTY(50)
*   COMMON/LTADM/LTADM(50)
*   COMMON/LTPROD/LTPROD(50)
*   COMMON/NBOTU/NBOTU(50)
*   COMMON/SRFOR/SRFOR,SRPLE,GDFOR
*
*   COMPUTE INVENTORY POSITION
*
*   NRS=NMAX-NLOCBK
*   INPOS=INVACT(N) + INVDUE(N) - NBOTU(N)
*   IF (IDBUG.EQ.1) WRITE(6,8013) INVACT(N), INVDUE(N), NBOTU(N), INPOS, NRS
8013  FORMAT(4X, '***STATN--UNITS ON=', I5, ' DUE-IN=',
*         I5, ' BO=', I5, ' INPOS=', I5, ' REQ-SHORT=', I5)
*
*   GO TO ASSIGNED SERVICEABLE RETURN MODEL
*
*   GO TO (91,91,92,92,92,92,91,91), ICDFOR
*
91  CONTINUE
*
*   MODELS 1,2,7 AND 8 FOR SERVICEABLE RETURNS
*
*   IS INVENTORY POSITION ON OR BELOW REORDER POINT
*
*   IEQ=IRQTY(N)
*   INVPOS=INPOS
99  IF (INVPOS .GT. IROL(N)) RETURN
*
*   COMPUTE TOTAL BUY QUANTITY (EQ + ROLDF)
*
97  IBO=IEQ + (IROL(N) - INVPOS)
*
*   COMPUTE DELIVERY DATES FOR ORDER
*
95  IDELIV=ITIME+ITMNTN*(LTADM(N)+LTPROD(N))
*
*   PLACE ORDER FOR IBO UNITS
```



1 04-16-77 12.102

STATN,  
P. 2 of 3

```
      CALL ORDER(N,IBQ,IDELIV)
      RETURN
*
92 CONTINUE
*
      COMPUTE AMENDED INVENTORY POSITION
*
      ISRPLT=SRPLT + .5
      IANPOS=INPOS + ISRPLT
      INVPOS=IANPOS
      IF(ICDFOR .EQ. 3) GO TO 99
      IF(ICDFOR .GE. 5) GO TO 94
*
      IS AMENDED INVENTORY POSITION ON OR BELOW REORDER POINT
      FOR MODEL 4 ONLY
*
      IF(INVPOS .GT. IROL(N)) RETURN
*
      COMPUTE PROCUREMENT CYCLE (EOQ PERIOD)
      AND SERVICEABLE RETURNS EXPECTED IN THIS CYCLE
*
94  IPC=(FLOAT(IQTY(N))/GDFOR) + .5
      ISRPC=FLOAT(IPC)*SRFOR + .5
*
      REDUCE REORDER QUANTITY (EOQ) BY EXPECTED SERVICEABLE RETURNS
      IN PROCUREMENT CYCLE
*
      IEQ=IQTY(N) - ISRPC
      IF(ICDFOR .GE. 5) GO TO 98
      IF(IEQ .LT. 0) IEQ=0
*
      COMPUTE BUY QUANTITY FOR MODEL 4
*
      INVPOS=INPOS
      GO TO 97
*
98 CONTINUE
*
      IS INVENTORY POSITION ON OR BELOW REORDER POINT FOR MODELS 5 AND 6
*
      IF(INPOS .GT. IROL(N)) RETURN
*
      COMPUTE TOTAL BUY QUANTITY FOR MODEL 5
*
      IBQ=IEQ + IROL(N) - INPOS
      IF(ICDFOR .EQ. 6) GO TO 96
      IF(IBQ .LE. 0) RETURN
      GO TO 95
*
96 CONTINUE
*
```

01 04-16-77 12.102

\* COMPUTE TOTAL BUY QUANTITY FOR MODEL 6  
\*

```
AEOQ=.5*FLOAT(IRQTY(N))  
IF(FLOAT(IBQ) .LE. AEOQ) IBQ=AEOQ + .5  
IF(FLOAT(IBQ) .GT. AEOQ) IBQ=IBQ  
IF(IBQ .LE. 0) RETURN  
GO TO 95  
END
```

STATN,  
p. 3 of 3

Subroutine: WRIFEL

Function:

This routine writes to File 06 all of the current elements in the Future Events List.

Description:

This routine provides a detailed listing of all information currently recorded in the Future Events List. See Volume I, Chapter IV for a detailed description of routines WRIFEL, INFEL, ENTER, and REMOVE.

02-11-77 10.614

WRIFEL

p. 1 of 1

```
SUBROUTINE WRIFEL
COMMON/NFIRST/NFIRST
COMMON/NENTRY/NENTRY
COMMON/JPOINT/JPOINT(500)
COMMON/JFSN/JFSN(500)
COMMON/JQTY/JQTY(500)
COMMON/JPRIOR/JPRIOR(500)
COMMON/JTYPE/JTYPE(500)
COMMON/JTIME/JTIME(500)
COMMON/LOCLE/LOCLE(500)
WRITE(6,8015)JTIME(NFIRST),NFIRST,NENTRY
8015 FORMAT(///20X,20HEVENTS LIST AT TIME ,3110//)
WRITE(6,8020)(K,JTIME(K),JTYPE(K),JFSN(K),JQTY(K),JPRIOR(K),JPOINT
C(K),K=1,NENTRY)
8020 FORMAT(500(10X,7F10//))
RETURN
END
```

Subroutine:    TERMIN

Function:

This routine terminates all or part of the most recent replenishment order (if any) still in the administrative phase.

Description:

Subroutine TERMIN terminates all or part of the latest buy (if any) still in the administrative phase (i.e. not yet on contract). The routine continues to terminate orders until either (a) total assets terminated equals the termination quantity or (b) all buys still in the administrative phase have been canceled, whichever occurs first.

By convention, outstanding orders are terminated by setting the order quantity to zero on the Future Events List, and updating the associated pointer structure. The associated receipt event is not removed from the Future Events List, however, until the originally scheduled due-in time.

Note: This routine was not used in the current study, and may not be compatible with other INSSIM subroutines.



12-09-76 21.855

TERMIN  
p. 1 of 2

```
SUBROUTINE TERMIN(KFSN, ITQ)
C      THIS ROUTINE TERMINATES ALL OR PART OF THE LATEST BUY(IE ANY)
C      STILL IN THE ADMINISTRATIVE PHASE (I.E. NOT YET ON CONTRACT)
C      UNTIL EITHER (1) TOTAL ASSETS TERMINATED EQUALS THE TERMINATION
C      QUANTITY (ITQ) OR (2) ALL BUYS STILL IN THE ADMINISTRATIVE PHASE
C      HAVE BEEN CANCELLED, WHICHEVER OCCURS FIRST.
COMMON/IDBUG/IDBUG
COMMON/IOBLIG/IOBLIG
COMMON/ITIME/ITIME
COMMON/ITMNTN/ITMNTN
COMMON/INVDUE/INVDUE(50)
COMMON/LTPROD/LTPROD(50)
COMMON/NORDPT/NORDPT(50)
COMMON/UCOST/UCOST(50)
COMMON/JQTY/JQTY(500)
COMMON/JTIME/JTIME(500)
COMMON/JPRIOR/JPRIOR(500)
COMMON/ITERM /ITERM(30,3)
COMMON/INVOR/INVOR(30,3)
IF(IDBUG.NE.1) GO TO 18
WRITE(6,8000)ITIME,KFSN,ITQ,NORDPT(KFSN)
8000 FORMAT(7H TERMIN,110,818)
18 CONTINUE
C      ARE THERE ANY ORDERS OUTSTANDING ON ITEM KFSN
IF(NORDPT(KFSN).IE.0) RETURN
C      OBTAIN LOCATION OF ORDER DATA ON FUTURE EVENTS LIST
20 KORD=NORDPT(KFSN)
C      COMPUTE THE DATE THAT THE MOST RECENT PURCHASE ORDER CLEARS
C      THE ADMINISTRATIVE PHASE.
25 IDUE=JTIME(KORD)
IADM=IDUE-ITMNTN*LTPROD(KFSN)
C      IS THE ORDER ALREADY ON CONTRACT
IF(IADM.LT.ITIME) RETURN
C      DOES THE ORDER QUANT. EXCEED THE TERMINATION QUANTITY.
IF(JQTY(KORD).LE.ITQ) GO TO 40
C      DECREASE THE ORDER BY THE TERMINATION QUANTITY.
JQTY(KORD)=JQTY(KORD)-ITQ
C      UPDATE ON-ORDER STATUS RECORDS
INVDUE(KFSN)=INVDUE(KFSN)-ITQ
IOBLIG=FLOAT(IOBLIG)-FLOAT(ITQ)*UCOST(KFSN)
JITQ=-ITQ
CALL CUM(ITERM,ITQ,KFSN)
CALL CUM(INVOR,JITQ,KFSN)
RETURN
C      *** NOTE ***
C      BY CONVENTION, OUTSTANDING ORDERS ARE TERMINATED BY SETTING
C      THE ORDER QUANTITY TO ZERO ON THE FUTURE EVENTS LIST,
C      AND UPDATING THE FSN CROSS REFERENCE STRUCTURE. THE RECEIPT
C      TRANSACTION IS NOT REMOVED FROM THE FUTURE EVENTS LIST HOWEVER
C      UNTIL THE ORIGINALLY ANTICIPATED DUE-IN-TIME.
C      UPDATE ON-ORDER STATUS RECORDS
```



TERMIN  
p. 2 of 2

11 12-09-76 21.855

```
40 KQTY=JQTY(KORD)
   JQTY(KORD)=0
   NORDPT(KFSN)=JPRTOR(KORD)
   INVDUE(KFSN)=INVDUE(KFSN)-KQTY
   IORLIG=FLOAT(IORLIG)-FLOAT(ITQ)*UCOST(KFSN)
   ITQ=-KQTY
   CALL CUM(ITERM,KQTY,KFSN)
   CALL CUM(INVOR,ITQ,KFSN)
   ITQ=ITQ-KQTY
C   ARE THERE ANY OTHER ORDERS OUTSTANDING ON ITEM KFSN
   IF(NORDPT(KFSN).GT.0) GO TO 20
   RETURN
END
```

Subroutine: ZERO

Function:

This routine zeros the INSSIM statistical accumulators.

Description:

This routine is called at the beginning of each INSSIM run to zero the variables for recording performance statistics, beginning on hand and on order stocks, and obligations.

ZERO

P. 1 of 2

```
10      $      IDENT    WP0287,ADDSC-CALLAHAN
20      $      FORTY    DECK
30      $      PRMFL    C*,W,S,REQS/ZERO.0
40      $      REMOTE    P*,AC
50      $      REMOTE    $$,AC
60      SUBROUTINE ZERO
70      COMMON/IOBLIG/IOBLIG
80      COMMON/IBOP/IBOP(3),IBOPOR(3)
90      COMMON/IBAUTH/IBAUTH(12)
100     COMMON/IBPROJ/IBPROJ(12)
110     COMMON/IBACKI/IBACKI(30,3)
120     COMMON/IBACKT/IBACKT(30,3)
130     COMMON/IBAKDI/IBAKDI(30,3)
140     COMMON/IBAKDT/IBAKDT(30,3)
150     COMMON/ICANCL/ICANCL(30,3)
160     COMMON/IDISPS/IDISPS(30,3)
170     COMMON/IEPED/IEPED(30,3)
180     COMMON/IFILLI/IFILLI(30,3)
190     COMMON/IFILLT/IFILLT(30,3)
200     COMMON/INVDAY/INVDAY(30,3)
210     COMMON/INVOH/INVOH(30,3)
220     COMMON/INVOR/INVOR(30,3)
230     COMMON/IORDER/IORDER(30,3)
240     COMMON/IRATON/IRATON(30,3)
250     COMMON/IRECET/IRECET(30,3)
260     COMMON/IREQC /IREQC(30,3)
270     COMMON/IREQI /IREQI(30,3)
280     COMMON/IREQT/IREQT(30,3)
290     COMMON/IRETRN/IRETRN(30,3)
300     COMMON/ISHIPI/ISHIPI(30,3)
310     COMMON/ISHIPT/ISHIPT(30,3)
320     COMMON/ITERM /ITERM(30,3)
0325    COMMON/ISMORD/ISMORD(30,3)
0326    COMMON/ILGORD/ILGORD(30,3)
0327    COMMON/IBOPCT/IBOPSM(3),IBOPLG(3)
330     C      ZERO STATISTICAL ACCUMULATORS
340     IOBLIG=0
350     DO 25 I=1,30
360     DO 25 J=1,3
370     ICANCL(I,J)=0
380     INVOH(I,J)=0
390     INVOR(I,J)=0
400     IRECET(I,J)=0
410     IRETRN(I,J)=0
420     INVDAY(I,J)=0
430     IORDER(I,J)=0
```

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER <b>AFOSR-77-1235</b>	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) <b>THE INVENTORY SYSTEM SIMULATOR (INSSIM), VOLUME II: PROGRAM LISTINGS AND NARRATIVES</b>		5. TYPE OF REPORT & PERIOD COVERED <b>Interim</b>
7. AUTHOR(s) <b>W. Steven Demmy</b>		6. PERFORMING ORG. REPORT NUMBER <b>RM 77-03</b>
9. PERFORMING ORGANIZATION NAME AND ADDRESS <b>Decision Systems 3575 Charlene Drive Dayton, OH 45432</b>		8. CONTRACT OR GRANT NUMBER(s) <b>F49620-77-C-0063</b>
11. CONTROLLING OFFICE NAME AND ADDRESS <b>Air Force Office of Scientific Research/NM Bolling AFB, DC 20332</b>		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS <b>61102F 2304/A5</b>
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		12. REPORT DATE <b>August 1977</b>
		13. NUMBER OF PAGES <b>116</b>
		15. SECURITY CLASS. (of this report) <b>UNCLASSIFIED</b>
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report)  <b>Approved for public release; distribution unlimited.</b>		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number)  <b>single-location, multi-item, EOQ, inventory, simulation model, FORTRAN</b>		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) <b>This report describes the features of the Inventory System Simulator (INSSIM), a FORTRAN-based simulation model of a general single-location inventory system. The model was specifically designed to evaluate alternate forecasting and inventory management policies proposed for use in the EOQ Buy Computation System (D062). Volume I of this report describes the philosophy, organization, and input/output features of INSSIM. Volume II documents the FORTRAN statement listings of each INSSIM program, and provides narratives describing the functions of each routine.</b>		

ZERO (CONT)

P 2 of 2

```
440      IDISPS(I,J)=0
450      ITERM(I,J)=0
460      IEXPED(I,J)=0
470      IRATON(I,J)=0
480      IREQC(I,J)=0
490      IREQT(I,J)=0
500      IREQI(I,J)=0
510      IBACKT(I,J)=0
520      IBACKI(I,J)=0
530      IBAKDT(I,J)=0
540      IBAKDI(I,J)=0
550      IFILLT(I,J)=0
560      IFILLI(I,J)=0
570      ISHIPT(I,J)=0
580      ISHIPI(I,J)=0
0585      ISMORD(I,J)=0
0586      ILGORD(I,J)=0
590      25 CONTINUE
600      C
610      C      ZERO ON-HAND AND ON-ORDER COUNTERS
620      C
630      DO 110 I=1,3
640      IBOPON(I)=0
650      IBOPOR(I)=0
0655      IBOPSM(I)=0
0656      IBOPLG(I)=0
660      110 CONTINUE
670      RETURN
680      END
690      $      ENDJOB
```